

Name: K-PLUS LOW SHOE	Code: MB2014B0	MB20 FOOTWEAR - ULTRA LIGHT SERIES
------------------------------	-----------------------	---

Description

Low shoe with a cutting-edge seamless upper in polyester mesh, abrasion

and tear resistant. Metal free.

Fibreglass toecap and composite midsole with constant thickness, PS-Type. S1PS.

SOLE: (EVA/RUBBER) Sole in highly expanded EVA material, with high anti-

shock power, which makes the shoes more flexible and lighter. Outsole in nitrile rubber which assures perfect adhesion on either dry or wet surfaces. SRC slip resistant.

INSOLE: Insole made of two-component material with shell in polyurethane

foam and memory PU having variable thickness: 4 mm at the front and 9 mm

in the heel area. Considerable anti-shock properties. Antistatic.

DRY PLUSLINING: In polyester, with high draining power due to the high absorbing properties of the fabric and structure.

Main features:

- Extremely lightweight, breathable and comfortable
- Seamless upper for better fit to the foot, tear and abrasion resistance
- High DurabilityCap System: high durability TPU overcap system
- T-FLEX composite midsole with constant thickness of 4 mm
- TPU rear support to optimize stability in the heel area
- Ergonomic and ultra-flexible Eva/rubber outsole that guarantees a high level of comfort
- Suitable for environments characterized by soils with low degree of roughness.

The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments.



Category II	Colours GREY	Available Sizes In stock: 36 - 47
Quantity/Carton 10	EC Standards EN ISO 20345  Safety Class: S1PS FO SR	Important Information Light industry, Handling and Logistics, Warehousing, Cleaning, Maintenance and Installations, Automotive. The footwear should be stored in a cool dry place, far from heat sources and direct light. Make sure footwear is in good condition, before use. If the shoes are damaged, replace them. Clean the footwear with a soft brush and water.
Dexterity		Storage and cleaning