

Ampacoll® DT

Mounting tape for dry construction



- > Robust and durable – excellent adhesive qualities
- > No chewing-gum effect, thanks to stable fibre inlay
- > Double-sided adhesive – for fast, staple-less installation

Technical details	Value
Storage	cool and dry
Application temperature	from -5°C
Temperature resistance	-40 to +80°C
Resistance to ageing	>20 years



Area of application: Double-sided adhesive tape for fast and durable fixing of vapour checks and metallic profiles in dry-wall constructions.

Delivery forms			
Article number	Identification	Roll size	Box content
7640115531667	Ampacoll® DT	50m×20mm×0,3mm	12 rolls = 600m

Application photos



Product information

The surfaces to be bonded must be clean, dry and free of dust and grease.

Double-sided adhesive mounting tape with a blue lattice insert and a solvent-free adhesive. For safe, durable fixing of vapor

barriers and vapor seals on a firm substrate, without stapling. Also suitable for damp protected bonding of roof and wall membranes.



Please observe the recommendations for use and further system products in our adhesives matrix



Further information and detailed documentation at www.ampack.biz

Sales via specialist dealers

Ampack Switzerland: 071 858 38 00
Ampack Austria: 05523 53433
Ampack Germany: 07621 1610264
Ampack France: 04 50 83 70 54
Ampack Italy: 0471 053 475

www.ampack.biz



The following information could have been superseded by new findings or developments.
Current Information can be found at www.ampack.biz. © Ampack AG, Rorschach, 05.2018