

Declaration of Performance No. DoP-24-112-01

Product name: Ampatex A primo plus

1 Unique identification code of the product type:

Ampatex A primo plus, CE 25 • EN 13984 • DoP-24-112

2 Intended use of the construction product as specified by the manufacturer in accordance with the applicable harmonised technical specification:

Vapour barrier or vapour control layer according to EN 13984 – Waterproofing membranes – Plastic and elastomeric vapour control layers – Definitions and characteristics

3 Manufacturer:

Ampack AG
Seebleichstrasse 50
CH-9401 Rorschach

5 System for assessing and verifying performance consistency:

System 3

6 Harmonised standard: EN

13984:2013 Notified bodies:

- APPLUS (0370)

- SKZ (1213)

7 Declared performance:

Essential characteristics			Performance		
	Method	Unit	Nominal value	Min	Max
Fire behaviour	EN 13 501-1	-	A2-s1,d0	-	-
Resistance to water passage	EN 1928		complies		
Water vapour permeability	EN 1931 – Method B	m	> 50		
Maximum tensile force longitudinal	EN 12 311-1	N/5 cm	2,750		
Maximum transverse tensile force	EN 12 311-1	N/5 cm	2,280		
Longitudinal elongation	EN 12 311-1		4.8		
Transverse elongation	EN 12 311-1	%	4.6		
Resistance to tearing lengthwise	EN 12 310-1	N	500		
Resistance to tearing across the grain	EN 12 310-1	N	500		
Cold bending behaviour	EN 1109	°C	-35		
Emissivity	EN 15976	%	5	-	+3
Hazardous substances	Must be declared	-	None		

8 The performance of the product corresponds to the declared performance in accordance with section 7:

Signed for and on behalf of the manufacturer in accordance with section 3

Rorschach, 27 June 2025



Lukas Deschwanden, Managing Director, Ampack AG, Rorschach