

DECLARATION OF PERFORMANCE

No. **DoP** – **019 TD-PP NTB**

- Unique identification code of the product-type: **TESSILDRAIN PP NTB 200**
- Intended use/es:
EN 13249:2000/A1:2005, EN 13250:2000/A1:2005, EN 13251:2000/A1:2005, EN 13252:2000/A1:2005, EN 13253:2000/A1:2005, EN 13254:2000/AC:2003/A1:2005, EN 13255:2000/AC:2003/A1:2005, EN 13257:2000/AC:2003/A1:2005, EN 13265:2000/AC:2003/A1:2005
- Manufacturer:
TESSILVENETA S.R.L.
Via Valgadana n°35/a - 36020 Valstagna (VI) – Italy
tel: 0424 92136 - fax: 0424 92154 - E-mail: info@tessilveneta.it
- Non applicable
- System/s of AVCP: Sistem 2+
- Harmonised standard:
EN 13249:2000/A1:2005, EN 13250:2000/A1:2005, EN 13251:2000/A1:2005, EN 13252:2000/A1:2005, EN 13253:2000/A1:2005, EN 13254:2000/AC:2003/A1:2005, EN 13255:2000/AC:2003/A1:2005, EN 13257:2000/AC:2003/A1:2005, EN 13265:2000/AC:2003/A1:2005

Notified body/ies:

Istituto Giordano S.p.A., the notified body n.0407

performed the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control under system 2+ and issued CE Certificate of **Factory Production Control n.0407-CPD-001 (IG-072-2004)**

- Declared performance/s:

Essential characteristics		Performance	Harmonised technical specification
Weight	EN ISO 9864	200 g/mq (+/-10%)	EN 13249:2000/A1:2005 EN 13250:2000/A1:2005 EN 13251:2000/A1:2005 EN 13252:2000/A1:2005 EN 13253:2000/A1:2005 EN 13254:2000/AC:2003/A1:2005 EN 13255:2000/AC:2003/A1:2005 EN 13257:2000/AC:2003/A1:2005 EN 13265:2000/AC:2003/A1:2005
Thickness 2 kP	EN ISO 9863-1	1,80 mm (+/-20%)	
Tensile strenght	EN ISO 10319	6,00 kN/m (-1 kN/m) 7,00 kN/m (-1 kN/m)	
MD			
CMD			
Elongation	EN ISO 10319	50% (+/-10%) 50% (+/-10%)	
MD			
CMD			
CBR puncture strenght	EN ISO 12236	1000 N (+/-10%)	
Cone drop test	EN ISO 13433	18,00 mm (+/-10%)	
Opening size	EN ISO 12956	83,01 micron (+/-10%)	
Water permeability normal to the plane	EN ISO 11058	3.58E-003 m/s (+/-30%)	
In-Plane flow capacity 20 kPa	EN ISO 12958	6,92E-003 l/m·s (+/-30%)	
Resistance to atmosphere agents	EN 12224	To be covered within 1 day after installation. Predicted to be durable a minimum of 5 years in natural soils with 4< pH <9 and soil temperature < 25°C	
Dangerous substances (National Regulations in force in EU Member States)		Less than required by national regulation in EU Member States	

- Not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
Luciano Campana
At Valstagna (VI) - ITALY on 11/11/2015

Luciano Campana