

1. Unique identification code of the product-type:

5902610524233

2. Intended use or uses:

The ceramic tiles for internal walls in buildings and industrial facilities.

3. Manufacturer:

Ceramika Paradyż Sp. z o.o., ul. Piotrkowska 61, 26-300 Opoczno, Polska

4. Authorized representative:

NA - not applicable

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

Assessment system: 4

6a. Harmonised standard:

EN14411

Notified unit/s:

NA - not applicable NA - not applicable

6b. European Assessment Document:

NA - not applicable

European Technical Assessment:

NA - not applicable

Technical Assessment Body:

NA - not applicable

Notified unit/s:

NA - not applicable

7. Declared performances:

Essential characteristics	Levels and/or classes	Reference document
Reaction to fire	A1	EN14411
Release of dangerous substances - glazed tiles:	-	-
- Lead [mg/dm ²]	≤ 0.8	EN14411
- Cadmium [mg/dm ²]	≤ 0.07	EN14411
- Other	NPD	EN14411
Bond strength / adhesion [N/mm ²]:	-	-
- cementitious adhesives	≥ 0.5	EN14411
- dispersion adhesives	≥ 1	EN14411
- reaction resin adhesives	≥ 2	EN14411
- mortar	NPD	EN14411
Thermal shock resistance	Pass	EN14411
Breaking strength [N]	minimum 600	EN14411
Slipperiness according to CEN/TS 16165:2016, Annex B	NA - not applicable	EN14411
Tactility	NPD - no performance determined	EN14411
Durability for:	-	-
- internal uses	Pass	EN14411
- external uses: freeze-thaw resistance	NA - not applicable	EN14411

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Karol Goździk - Production Manager

Tomaszów Mazowiecki date 2023-01-03



Applies to the product: PLACE OF SHINE PLUM ŚCIANA REKT. POŁYSK 29,8X89,8 G1
Group: BIII

1. Detailed information about the application:

Tiles should be protected from low temperatures.

Characteristics	Levels and/or classes	Reference document
Thickness	9.0 mm	EN14411
The permissible deviation of the average width for each tile from the work size width	± 0.5 %; ± 2.0 mm	EN14411
The permissible deviation of the average length for each tile from the work size length	± 0.5 %; ± 2.0 mm	EN14411
The permissible deviation of the average thickness of each tile from the work size thickness	± 10 %; ± 0.5 mm	EN14411
The maximum permissible deviation from straightness, related to the corresponding work size (width)	± 0.3 %; ± 1.5 mm	EN14411
The maximum permissible deviation from straightness, related to the corresponding work size (length)	± 0.5 %; ± 1.5 mm	EN14411
The maximum permissible deviation from rectangularity related to the corresponding work size (width)	± 0.5 %; ± 2.0 mm	EN14411
The maximum permissible deviation from rectangularity related to the corresponding work size (length)	± 0.5 %; ± 2.0 mm	EN14411
The maximum permissible deviation from flatness centre curvature, related to diagonal calculated from the work sizes	+ 0.5 % / - 0.3 %; + 2.0 mm / - 1.5 mm	EN14411
The maximum permissible deviation from flatness edge curvature, related to the corresponding work size (width)	+ 0.5 % / - 0.3 %; + 2.0 mm / - 1.5 mm	EN14411
The maximum permissible deviation from flatness edge curvature, related to the corresponding work size (length)	+ 0.5 % / - 0.3 %; + 2.0 mm / - 1.5 mm	EN14411
The maximum permissible deviation from flatness warpage, related to diagonal calculated from the work sizes	± 0.5 %; ± 2.0 mm	EN14411
Water absorption E_b [%]	> 10	EN14411
Breaking strength [N]	minimum 600	EN14411
Flexural tensile strength [N/mm ²]	minimum 12	EN14411
Resistance to deep abrasion - unglazed tiles [mm ³]	NA - not applicable	EN14411
Resistance to surface abrasion - glazed tiles, PEI/number of rotations	NA - not applicable	EN14411
Crazing resistance - glazed tiles	Pass	EN14411
Impact resistance	NPD - no performance determined	EN14411
Resistance to staining	minimum 4 class	EN14411
Resistance to low concentrations of acids and alkalis	LA class	EN14411
Resistance to high concentrations of acids and alkalis	NA - not applicable	EN14411
Resistance to household chemicals and swimming pool salts	A class	EN14411
Natural radioactivity [Bq/kg]	f1 ≤ 1, f2 ≤ 240	EN14411
Poślizg - BOSA STOPA	NA - not applicable	DIN EN 16165:2023-02, Attachment A
Poślizg - BOSA STOPA $\alpha_{barefoot}$ [°]	NA - not applicable	EN 16165:2023-02, Attachment A
Slip resistance acc. to CEN/TS 16165:2016, Appendix A (BARE FOOT)	NA - not applicable	DIN EN 16165:2023-02, Attachment B
Slip resistance acc. to CEN/TS 16165:2016, Appendix C (PTV) - risk of dry/wet slippage - slider 55	NA - not applicable	BS 7976-2:202+A1:2013 / UKSRG
Slip resistance acc. to CEN/TS 16165:2016, Appendix C (PTV) - risk of dry/wet slippage - slider 96	N/A - not applicable	BS 7976-2:202+A1:2013 / UKSRG
Displacement area class / displacement surface	NA - not applicable	DIN 51130
Emissions of volatile organic compounds (VOCs) - class	A+	ISO 16000
Thermal conductivity coefficient [W/m*K]	NPD - no performance determined	PN-EN 12664
Safety class of glass products	NA - not applicable	PN-EN 12600

2. Documents

Certificate of product compliance with the Polish Standard No. 52/N/22; Certificate authorising the product to bear the safety mark No. 51/B/22; Hygienic Certificate No. B-BK-60211-0341/21.

Signed for and on behalf of the manufacturer by:

Karol Goździk - Production Manager
Tomaszów Mazowiecki date 2023-01-03

