KBS11A

JOGI

Refrigerated counter-EN60x40-AISI304-Pastry&Bakery

One-piece structure in AISI 304 stainless steel. Temperature ranges: -2/+8°C. Worktop in AISI 304 stainless steel with splashback. EN 60x40cm. 1 door. Control panel digital thermometer - thermostat and communication port, possibility of adjusting the relative humidity to 75% or to 90%.



(€

General in	torm	ation
------------	------	-------

Supplier/producer 's name	SAGI
Series	Pastry & Bakery
Supplier's model identifier	KBS11A
Category	counter cabinet
Туре	refrigerated counter
Line	pastry & bakery - EN 60x40

Technical features

Temperature ranges, °C	-2/+8
Energy Efficiency Class	С
Energy consumption, kWh/24h	2,176
Energy consumption/year, kWh/a	794
Method for energy consumption	EN 22041
Energy Efficiency Index	37,88
Net usable volume, It	120
Volume, gross, lt	193
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 $^{\circ}\text{C}$
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,07
LWA dB(A)	46
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic electric type

Refrigerated counter-EN60x40-AISI304-Pastry&Bakery





KBS11A



Evaporation of condense drain	automatic	
Refrigeration power at -10°C W	465	
Frequency/voltage	230V 1N~ / 50Hz	
Electric power, kW	0,3	
nstruction features		
Structure	one-piece structure with rounded internal corners	
External material	AISI 304 stainless steel	
Internal material	AISI 304 stainless steel	
Internal bottom	with rounded corners	
Insulation thickness, mm	55	
Worktop	worktop 50 mm thick in AISI 304 stainless steel, with soundproofing lining; with splashback(h=8,5cm)	
Internal structure	AISI 304 stainless steel grid-supporting rack	
Positions (n.)/spaced, mm	7/75	
Evaporator	with an anti-corrosion treatment	
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condenser	
Feet	stainless steel AISI 304, adjustable in height	
Height of feet, mm	140 ÷ 200	
Equipped with	1 door	
ntrol and functions		
Kinf of control	thermometer-thermostat, communication port, possibility adjusting relative humidity to 75% or to 90%	
Display	digital	
Alarms	optical	
ndard		
Shelf's dimensions, cm	EN 60x40	
Shelves and couple of guides	7 pair of AISI 304 stainless steel runners for section	
nensions and weights		
Packing (LxDxH), cm	115x82x115	
Dimensions (LxDxH), cm	110x80x96,5	
Gross Weight (kg)		

105

Refrigerated counter-EN60x40-AISI304-Pastry&Bakery



Net Weight (kg)