## KC8ASX

# JOGI

## Refrigerated display unit+14/+16°C Luxor New Style

Display compartment in tempered glass throughout, black screen-silk printed. Glass door with invisible full-height handle. Hinge positioned on the left side. Lower structure in black color. Electronic p.c.b. HACCP alarms. Ventilated refrigeration. Setting of relative humidity through humidistat.Connection to APO.LINK portal for remote control of appliance through accessory (Industry 4.0)



 $\epsilon$ 

#### **General information**

Supplier/producer 's name	SAGI
Series	Luxor New Style
Supplier's model identifier	KC8ASX
Category	upright refrigerated display units
Туре	refrigerated display unit
Line	catering - pastry&bakery - ice-cream

#### **Technical features**

Temperature ranges, °C	+14+16
Relative humidity (%)	40÷44%
Energy Efficiency Class	product excluded from the European energy classification label according to EU Regulation 2019/2018
Volume, gross, lt	457
Climate class	4 (+30°C, 55% R.H.)
Refrigerant/GWP	R290/3
LWA dB(A)	65
Cooling system	ventilated refrigeration system
Evaporation of condense drain	automatic
Refrigeration power at -10°C W	425
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,36

#### **Construction features**

Display compartment

completely in tempered glass with black screen-silk printed (RAL 9005), anti-condense heating elem.





Refrigerated display unit+14/+16°C Luxor New Style

Lower structure

LED lighting	high luminous intensity anti-glare, possibility to change the type of light*
Door	1 glass door
Standard hinging door	on the left / no-reversible on the site
Door handle	"invisible" full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Evaporator	positioned in the lower part of the structure
Easymaintenance	accessibility to all the functional and control components
Safety interlock switch	yes, to stop internal fan
Feet	nr.4 integrated wheels, hidden by the structure
trol and functions  Kinf of control	electronic control board with the communication port and signaling
trol and functions Kinf of control	electronic control board with the communication port and signaling HACCP alarms
trol and functions  Kinf of control  Display	electronic control board with the communication port and signaling HACCP alarms digital with digit blue
trol and functions  Kinf of control  Display  Alarms	electronic control board with the communication port and signaling HACCP alarms digital with digit blue optical and acoustical
trol and functions  Kinf of control  Display	electronic control board with the communication port and signaling HACCP alarms digital with digit blue
trol and functions  Kinf of control  Display  Alarms	electronic control board with the communication port and signaling HACCP alarms digital with digit blue optical and acoustical
trol and functions  Kinf of control  Display  Alarms  Connectivity	electronic control board with the communication port and signaling HACCP alarms digital with digit blue optical and acoustical with APOLINK accessory for remote control – Industry 4.0 PIR Sense proximity sensor, changes light intensity as customers
Kinf of control  Display Alarms Connectivity Functions/programs	electronic control board with the communication port and signaling HACCP alarms digital with digit blue optical and acoustical with APOLINK accessory for remote control – Industry 4.0 PIR Sense proximity sensor, changes light intensity as customers
Kinf of control  Display Alarms  Connectivity  Functions/programs	electronic control board with the communication port and signaling HACCP alarms digital with digit blue optical and acoustical with APOLINK accessory for remote control – Industry 4.0 PIR Sense proximity sensor, changes light intensity as customers approach

black color (RAL 9005)

#### Dimensions and weights

Packing (LxDxH), cm	89x76x202
Dimensions (LxDxH), cm	80,5x64,5x184
Gross Weight (kg)	247
Net Weight (kg)	222

### **Notes**

- installation allowed to an altitude up to 800 meters above sea level Notes

\*3000K-4000K-5000K-6000K

