# KFSDR2N

# JOGI

# PASTRY REFRIGERATOR 60x80 cm, ONE DOOR, POS.TEMP.

Exterior/interior in AISI304 18-10 s/steel. Ventil. cooling system with finned evaporator. Electronic

thermometer/thermostat. Automatic defrosting electric type, automatic evaporation of condense drain AISI304 18-10 s/s handle and remov. shelf supports. Compartm.  $60 \times 80$  suitable for remote cooling unit.



**(**E

### **General information**

Supplier/producer 's name	SAGI
Series	Pastry & Bakery
Supplier's model identifier	KFSDR2N
Category	vertical cabinet
Туре	refrigerator
Line	pastry & bakery - EN 60x80

### **Technical features**

Temperature ranges, °C	-2/+8
Energy Efficiency Class	product are excluded from the European energy classification label according to EU Regulation 2015/1
Method for energy consumption	EN 16825
Climate class	5 (+40°C, 40% R.H.)
Cooling system	ventilated refrigeration system
Defrosting	automatic by heating elements
Evaporation of condense drain	automatic
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,4

### **Construction features**

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	diamond treated bottom with drain hole
Insulation thickness, mm	75

ANGELO PO GRANDI CUCINE S.p.a. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy





# PASTRY REFRIGERATOR 60x80 cm, ONE DOOR, POS.TEMP.

# KFSDR2N



KESUKZIN	
Door	1 door in AISI 304 stainless steel
Standard hinging door	on the right / reversible on the site with self-closing device for openings inferior to 90°
Door handle	integrated full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	40/30
Evaporator	positioned outside the compartment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	105 ÷ 155
Control and functions	
Kinf of control	electronic pannel control board
Display	digital
Alarms	optical and acoustical
Functions/programs	Hyper Cold - Energy Saving - setting of the relative humidity to 75% or to 90%
Standard	
Key-lock	yes
Lighting	yes
Couple of guides (n.)	20 pair of AISI 304 stainless steel runners

# **Dimensions and weights**

Packing (LxDxH), cm	89x106,5x213
Dimensions (LxDxH), cm	82x100x204
Gross Weight (kg)	170
Net Weight (kg)	152

### Notes

Notes absorption while defrosting





