



## TECHNICAL SPECIFICATIONS

Program and temperature display. The machine is controlled by an electronic digital display remote control mounted on the front panel. Large control panel where you can program flexibly and freely. In case of power outage, there is the option to continue the program from where it left off. The machine is controlled by an electronic digital display remote control mounted on the front panel. The device has 10 adjustable programs. There is also an emergency stop button on the front panel for use in emergencies. Energy-saving, fully insulated outer drum. There is a two-way rotating drum. Thanks to the two-way rotation feature of the drum, the laundry is dried in a shorter time. There is a safety switch on the loading/unloading cover. Thanks to the door lock system, it is ensured that the machine does not work if the door is open. There is a safety curtain that completely covers the rear part of the machine. The carcass is painted with electrostatic powder paint. Thanks to its superior adhesion feature, it shows great resistance to corrosion, mechanical and chemical impacts, heat and weather conditions and provides quality coating.

## GENERAL FEATURE

Space-saving ergonomic design. Large loading and unloading cover allowing easy loading. Control panel that allows you to easily carry out the laundry drying process and manage it perfectly and easily. With electric heating and cooling system. Large, easy access air filter. High and low drying speed (40 D/D 28 D/D).

## CONSTRUCTION FEATURES

Electrostatic powder coated carcass, AISI 304 quality stainless steel drum and AISI 304 quality stainless steel loading/unloading lid.

## SAFETY EQUIPMENT &

## APPROVALS

There is CE certification for all directives and regulations.

<b>PRODUCT CODE</b>	VLTD15
<b>DIMENSIONS</b>	1085x1025x1720 mm
<b>PACKAGE SIZES</b>	1125x1065x1770 mm
<b>WEIGHT</b>	310 kg
<b>PACKAGE WEIGHT</b>	325 kg
<b>TOTAL POWER</b>	14,8 kW
<b>HEATING POWER</b>	13,5 kW
<b>FAN POWER</b>	540 W
<b>DRUM CAPACITY</b>	15 kg 310 lt
<b>MOTOR POWER</b>	750 W
<b>ELECTRICAL VOLTAGE</b>	380-400 VAC 3N 50 Hz
<b>CABLE CROSS SECTION</b>	5X4 mm <sup>2</sup>

EI=ELECTRICAL CONNECTION  
D=DRAINAGE

