



### TECHNICAL SPECIFICATIONS

Since the iron is mono block, it can be easily used by the operator. In order to prevent risks such as finger entrapment during use, safety precautions have been taken with a protection switch. Ironing belts are made of "Nomex" material resistant to 220°C high temperature. All controls are placed on the front of the machine and are easy to use. There is a clamshell section that protects the electrical and gas components. Thanks to its special design, it operates without noise and with minimum vibration level, providing low energy consumption and high efficiency. Safety thermostat against overheating. The carcass is painted with electrostatic powder paint. Thanks to its superior adhesion feature, it shows great resistance against corrosion, mechanical and chemical impacts, heat, weather conditions and provides quality coating. It has pressure rollers that provide excellent ironing quality. It provides faster ironing thanks to its extended heat transfer surface.

### GENERAL FEATURE

Easy to use, manual control panel. Galvanized roller for better heat conduction. Two-way rotary belt system. Stainless steel hood adapted to the machine to collect moisture and steam. Quiet operation and superior ironing quality.

### CONSTRUCTION FEATURES

Powder coated carcass and galvanized cylinder.

### SAFETY EQUIPMENT &

### APPROVALS

CE certification for all directives and regulations.

<b>PRODUCT CODE</b>	VLRI75200G
<b>DIMENSIONS</b>	3000x1580x1900 mm
<b>PACKAGE SIZES</b>	3050x1630x1950 mm
<b>WEIGHT</b>	1885 kg
<b>PACKAGE WEIGHT</b>	2015 kg
<b>TOTAL POWER</b>	32 kW
<b>CYLINDER DIMENSION</b>	750x2000
<b>MOTOR POWER</b>	1,5 kW
<b>ELECTRICAL VOLTAGE</b>	380-400 VAC 3N 50 Hz
<b>CABLE CROSS SECTION</b>	5X1.5 mm <sup>2</sup>
<b>INJECTOR</b>	NG (G20) 2.40 mm
	LPG (G30) 2.00 mm
<b>GAS INLET</b>	R 3/4
<b>GAS COMSUMPTION</b>	3.387 max. / 1.778 min G20(m <sup>3</sup> /h)
	2.524 max. / 1.325 min. G30 (kg/h)

EI=ELECTRICAL CONNECTION

G=GAS GİRİŞİ

