

5MP ColourHunter HD Fixed Mini Bullet Analog Camera

UAC-B115-F28-W

UAC-B115-F40-W



Introduction

UAC-B115-F28/F40-W is a 5MP ColourHunter HD Fixed Mini Bullet Analog Camera with a high-performance 1/2.7-inch CMOS sensor. It supports TVI/AHD/CVI/CVBS, which effectively enhances product adaptability and diversity of networking solutions. With SYV-75-3 or other coaxial cable types the camera can achieve low-cost, long-distance, anti-interference, and low delay mega-pixel HD video transmission. The camera supports 24/7 full-color imaging.

Features


- 5MP high quality image
- TVI/AHD/CVI/CVBS
- Supports white light illumination, 24/7 full-color imaging
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages

Specifications

Model	UAC-B115-F28-W		UAC-B115-F40-W	
Sensor				
Pixel	5MP			
Size	1/2.7"			
Minimum illumination	0.02 lux (F1.6, AGC ON) 0.00 lux (white light on)			
Lens				
Lens	2.8mm		4.0mm	
Lens mount	M12			
Angle of view	H: 110.0° V: 57.0° D: 130.0°		H: 90.0° V: 48.0° D: 109.1°	
Illuminator				
Illuminator	One white-light illuminator			
Illumination distance	20m			
Lifetime	≥60,000 hours			
Video				
Resolution	5MP@25fps: 2880(H)×1620(V); 5MP@20fps: 2592(H)×1944(V); 5MP@12.5fps: 2592(H)×1944(V) 4MP: 2560(H)×1440(V) 1080P: 1920(H)×1080(V)			
Frame rate	TVI: 5MP@20fps, 5MP@12.5fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps AHD: 5MP@20fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps CVI: 5MP@25fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps CVBS: PAL/NTSC			
Shutter time	PAL: 1/25s-1/50000s NTSC: 1/30s–1/50000s			
Image				
Exposure mode	4 modes: Global (default), BLC, HLC, DWDR			
Day/Night	24/7 full-color imaging			
Digital noise reduction	2D			
White balance	Two modes: Auto (default), Manual			
WDR	DWDR			
Flip	Supports 180° horizontal flip, 180° vertical flip			
Interface				
Power	5.5mm power interface			
Video output	BNC, supports TVI/AHD/CVI/CVBS			
Operating environment				
Temperature	-30°C to 60°C(-22°F to 140°F)			
Humidity	≤95% (RH, non-condensing)			
Surge protection	4KV			
Ingress protection	IP67			

General	
Power	DC12V ($\pm 25\%$), with reverse polarity protection and surge protection, Max 2.4W
Mount	3D bracket supplied, surface mount (default), optional backbox, pole mount bracket
Dimensions	142mm*63mm*65mm (L*W*H)
Material	Plastic
Weight	145g(0.32lb)
Certification	CB, CE, FCC

Dimensions



UAC-B115-F28/F40-W

Ordering Information

Model	Remarks
UAC-B115-F28-W	5MP ColourHunter HD Fixed Mini Bullet Analog Camera (2.8mm fixed-focal lens, DC12V)-Overseas version, power adapter sold separately
UAC-B115-F40-W	5MP ColourHunter HD Fixed Mini Bullet Analog Camera (4.0mm fixed-focal lens, DC12V)-Overseas version, power adapter sold separately

Accessory Model	Image	Remarks
TR-JB05-A-IN		Bullet camera backbox (supports rear cabling, square)-97.5mm*93mm*43.1mm, sold separately
TR-UP06-B-IN		Bullet camera pole-mount bracket (white)-bullet camera-sheet metal, sold separately
TR-JB07-D-IN		Bullet camera backbox (supports rear cabling)--125mm*125mm*57mm, sold separately

Zhejiang Uniview Technologies Co., Ltd.

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China (310051)

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2022 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.