

Overview

Deploy the UniFi AC Pro AP indoors or outdoors, in wireless networks requiring maximum performance. Sporting a weatherproof design, the UniFi AC Pro AP features simultaneous, dual-band, 3x3 MIMO technology and convenient 802.3af PoE/802.3at PoE+ compatibility.

Quick Specs

Figure 1 shows the appearance of UAP-AC-PRO.



Table 1 shows the Quick Specs.

SKU	UAP-AC-PRO
Dimensions	196.7 x 196.7 x 35 mm (7.74 x 7.74 x 1.38")
Networking Interface	(2) 10/100/1000 Ethernet Ports
Ports	(1) USB 2.0 Port
Buttons	Reset
Antennas	(3) Dual-Band Antennas, 2.4 GHz: 3 dBi, 5 GHz: 6 dBi
Wi-Fi Standards	802.11 a/b/g/n/ac
Power Method	Passive Power over Ethernet (48V), 802.3af/803.2at Supported (Supported Voltage Range: 44 to 57VDC)
Maximum Power Consumption	9W
Max TX Power	22 dBm

Product Details

Figure 2 shows the front panel ofUAP-AC-PRO.



Figure 3 shows the back panel of UAP-AC-PRO.



UAP-AC-PRO provides these features:

- (1) Simultaneous Dual-Band 3x3 MIMO
- (2) 5 GHz Band with Speeds of up to 1300 Mbps
- (3) 2.4 GHz Band with Speeds of up to 450 Mbps
- (4) Range up to 122 meters (400 feet)
- (5) 802.3af PoE / 802.3at PoE+ Compatible
- (6) (2) Gigabit Ethernet Ports

Table 2 shows the supported switches.

Product Name	Details
US-8	UBNT UniFi US-8 Enterprise PoE 8-Port Managed PoE Gigabit Switch
US-8-60W	UBNT US-8-60W UniFi 8-Port Gigabit PoE Compliant Managed Switch, Enterprise
US-8-150W	UBNT UniFi US-8-150W Enterprise PoE 8-Port Managed PoE Gigabit Switch
US-16-150W	UBNT UniFi US-16-150W Enterprise PoE 16-Port Managed PoE Gigabit Switch
US-24	UBNT US-24 UniFi 24-Port Gigabit PoE Compliant Managed Switch, Enterprise
US-24-250W	UBNT UniFi US-24-250W Enterprise PoE 24-Port Managed PoE Gigabit Switch

Compare to Similar Items

Table 3 shows the comparison.

Product Name	UAP-AC-PRO	UAP-AC-LITE	UAP-AC-IW with Gigabit PoE Power Supply
Dimensions	196.7 x 35 mm	160 x 31.45 mm	139.7 x 86.7 mm

Environment	Indoor/Outdoor	Indoor	Indoor
2.4 GHz Radio Rate	450 Mbps	300 Mbps	300 Mbps
5 GHz Radio Rate	1300 Mbps	867 Mbps	867 Mbps
PoE Mode	802.3af PoE/802.3at PoE+	802.3af/A PoE & 24V PoE	802.3at PoE+
Ports	(2)10/100/1000 Ethernet	(1)10/100/1000 Ethernet	(3)10/100/1000 Ethernet

Get More Information

Do you have any question about the UAP-AC-PRO?

Contact us now via [Live Chat](#) or sales@router-switch.com.

Specification

UAP-AC-PRO Specification	
Dimensions	196.7 x 196.7 x 35 mm (7.74 x 7.74 x 1.38")
Networking Interface	(2) 10/100/1000 Ethernet Ports
Ports	(1) USB 2.0 Port
Buttons	Reset
Antennas	(3) Dual-Band Antennas, 2.4 GHz: 3 dBi, 5 GHz: 6 dBi
Wi-Fi Standards	802.11 a/b/g/n/ac
Power Method	Passive Power over Ethernet (48V), 802.3af/803.2at Supported (Supported Voltage Range: 44 to 57VDC)
Maximum Power Consumption	9W
Max TX Power	22 dBm
BSSID	Up to Four per Radio
Power Save	Supported
Wireless Security	WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES)
Certifications	CE, FCC, IC
Mounting	Wall/Ceiling (Kits Included)
Operating Temperature	-10 to 70° C (14 to 158° F)
Operating Humidity	5 to 95% Noncondensing
ADVANCED TRAFFIC MANAGEMENT	
VLAN	802.1Q
Advanced QoS	Per-User Rate Limiting
Guest Traffic Isolation	Supported
WMM	Voice, Video, Best Effort, and Background
Concurrent Clients	200+
SUPPORTED DATA RATES (MBPS)	

802.11a	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11n	6.5 Mbps to 450 Mbps (MCS0 - MCS23, HT 20/40)
802.11ac	6.5 Mbps to 1300 Mbps (MCS0 - MCS9 NSS1/2/3, VHT 20/40/80)
802.11b	1, 2, 5.5, 11 Mbps
802.11g	6, 9, 12, 18, 24, 36, 48, 54 Mbps

Want to Buy

[Order Now](#)

[Get a Quote](#)

Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.


200+
Countries we Sold


18,000+
Customers Trusted


\$20,000,000
Inventory Available


50%-98%
Off Global List Price


100%
Safe Online Shopping

Contact Us

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com