

HWI-D149H(2.8mm)(D)

HIKVISION Hiwatch



HIKVISION Hiwatch HWI-D149H(2.8mm)(D). IP Dome Camera. 1/2.8" Progressive Scan CMOS ColorVu. 4 Megapixel (2560x1440). Lens 2.8 mm. Color image 24/7. WDR. 3DNR. H.265+. RJ-45 10/100 . aseT. PoE IEEE802.3af. WEB interface, CMS, Smartphone and NVR. ONVIF compatible. IP67 waterproof. Antivandal IK08 Hwi-d149h(2.8mm)(d).

Specifications

- HiWatch Series Range
- Image Sensor: 1/2.8" Progressive Scan CMOS
- Maximum resolution: 4 Megapixel (2560x1440)
- Stream 1: 4Mpx (20 FPS), 1080p / 720p (25 FPS)
- Stream 2: D1 / CIF (1 ~ 25 FPS)
- Compresión: H.265+/H.265/H.264+/H.264
- Bitrate: 32 Kbps ~ 8 Mbps
- Lens: 2.8 mm
- Lens Positioning: 2 Axis
- Minimum Illumination: Color 0.01 Lux @ F1.2 | Color 0.028 Lux @ F2.0
- Visible Illumination: 0 Lux / Supplementary Light (White): 30 m
- Image enhancements: WDR, BLC, 3D-NR, AGC, Motion detection
- Day / Night Removable mechanical ICR filter
- Network interface: Ethernet 10/100 BaseT
- Remote access: Web browser, Smartphone App IVMS 4500 and
- PC Software IVMS 4200
- Interoperability: ONVIF, PSIA, CGI, ISAPI
- Power supply: DC 12 V / 500 mA, PoE IEEE802.3af
- Degree of protection: IP67, IK10
- Material: Plastic
- Operating temp.: -30° C ~ +50° C
- Dimensions: 97.6 mm (Fo) x 121.5 (Ø) mm
- Weight: 500 g

- HIK-444

