



Reolink Innovation Limited

Picture



Model

Argus Series B430

Video & Audio	Image Sensor	1/2.7"CMOS sensor
	Resolution	2880 x 1616 (5 megapixels) @15fps
	Video Compression	H.265
	Field of View	Horizontal: 90°
		Vertical: 47°
		Diagonal: 110°
	Infrared Night Vision	Up to 10 meters (33ft); LED: 2pcs/1.2w/850nm (Auto-switching with IR-cut filter)
	Color Night Vision	With spotlights: 2pcs/2.4w/6500k
	Frame Rate	Main stream: 10fps - 15fps (default: 15fps)
		Sub stream: 10fps - 15fps (default: 15fps)
Power Requirements	Battery	Main stream: 1024Kbps - 4096Kbps (default: 3072Kbps)
		Sub stream: 64Kbps - 672Kbps (default: 672Kbps)
Interface	Audio	Two-way audio
	Power Port	USB Type-C port
	SD Card Slot	Supports Max. 128GB microSD card
	Reset Button	YES
Pan & Tilt	Audio In/Out	Built-in microphone and speaker
	PT Angle (Max.)	Pan: 355°, Tilt: 140°
Wi-Fi	Preset Points	32
	Wireless Standard	IEEE 802.11 a/b/g/n
	Operating Frequency	2.4GHz/5GHz
Software	Wireless Security	WPA/WPA2
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Protocols & Standards	SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P
Other Features	User Access	Max. 12 simultaneous streams (2 main & 10 sub streams)
	Smart Alarm	PIR detection, person detection, vehicle detection, pet detection
	PIR Detecting Distance	Adjustable up to 10m (33ft)
	PIR Detecting Angle	120° horizontal
	Recording Modes	Triggered recording
	Time Lapse	YES
	Smart Home Compatibility	Google Assistant; Alexa
Working Environment	Cloud Storage	Supports Reolink Cloud (available in selected countries)
	Operating Temperature	-10°C~+55°C (14°F~131°F)
	Operating Humidity	20% ~ 85%
Mechanical	Weatherproof	IP64
	Dimensions	Φ98 x 122mm
Warranty	Weight (Battery Included)	477g
	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .