replink **Reolink Innovation Limited Picture Trackmix Series B770** Model 1/3"+1/2.7"CMOS Sensor Image Sensor Video Resolution UP To:3840 x 2160 (8.0 Megapixels) at 15 frames/sec f=2.8mm@F=1.6, f=8mm@F=1.6 Lens Video Format H.264,H.265 Horizontal: 108°-38° Video & Field of View Vertical: 57°-21° **Audio** Zoom Mode 6X hybrid zoom Day & Night IR-cut filter with auto-switching Infrared Night Vision Up to 30Meters (90ft)(LED: 2pcs/850nm) Color Night Vision Spotlight: 1pcs/6500K/450 Lumens(15m) Audio Two-way Audio 5100mAh rechargeable battery (Battery life varies based on settings, usage & Battery temperature) Power Solar Reolink Solar Panel 2 5V/2A DC Power Power USB Type-C port Reset Button System Interface Storage MicroSD card slot (Max. 128GB) Audio Built-in Microphone and Speaker Pan: 355°, Tilt: 0°~90°; (Speed can be set) Pan &Tilt Pan&Tilt Preset Auto Tracking Support IEEE 802.11a/b/g/n Wireless Standard Wi-Fi 2.4GHz/5GHz Operating Frequency Wireless Security WPA-PSK/WPA2-PSK Main Stream: 10fps - 15fps Frame Rate Sub Stream: 10fps - 15fps Main Stream: 1024Kbps -4096Kbps Code Rate Sub Stream: 64Kbps -672Kbps PC: Windows, Mac OS; Smartphone: iOS, Android Software OS Supported **Features** PIR Detection/Human Detection/Vehicle Detection/Pet Detection Smart Alarm Record Mode Motion Triggered Recording SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P Maximal User Access Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams) Work with Google Assistant, Reolink Cloud

Temperature

Humidity

Waterproof

Dimension

Weight

Limited Warranty

Working

Environment

Size &

Weight

Warranty

Operating Temperature: -10°C~+55°C (14°F~131°F)

Operating Humidity: 20% ~ 85%

Support 228*147*129mm

1.4KG

2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/