

DS-3WRU3X
AX300 Wi-Fi 6 Nano USB Adapter



- Upgrade to WiFi 6 For Better Experience
- Auto-install, Plug And Play
- Compatible with Various Operating Systems




▪ Specification

General	
Product Dimension (W × H × D)	21mm×15mm×7.7mm
Package Dimension (W × H × D)	95mm×98mm×120mm
Net Weight	0.002 kg
Packing List	Wireless USB Adapter × 1 Quick Start Guide × 1 Regulatory Compliance and Safety Information × 1
Packing Method	Single pack
Working Temperature	0 °C to 40 °C (32 °F to 104 °F)
Working Humidity	10% to 90% RH non-condensing
Storage Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Storage Humidity	30% to 90% RH non-condensing
Max. Power Consumption	≤ 1.25 W
Gross Weight	0.021 kg
Wireless Parameter	
Data Rate	≤ 300 Mbps 2.4 GHz: Up to 286Mbps
Wireless Standard	IEEE802.11ax/b/g/n
Working Frequency Band	2.4 GHz
Transmitting Power	<20dBm (EIRP) <0.1W(EIRP)
Wireless Performance	1*1 MIMO supported
Receiving Sensitivity	2.4 GHz 11b-1M:-96dBm 11g-6M:-94dBm 11n-20M-MCS7:-75dBm 11n-40M-MCS7:-72dBm 11ax-HT20M-MCS9:-69dBm 11ax-HT40M-MCS9:-66dBm
Antenna	Internal Antenna
Hardware Parameter	
Power Supply Method	USB
Software Function	
Application function	Station Mode , Soft AP Mode
Security Mode	Default encryption mode: Mix WPA-PSK/WPA2-PSK WPA algorithm: TKIP
Supported Operating System	win7/10/11/linux

▪ Available Model

DS-3WRU3X(0-STD)

▪ Dimension



See Far, Go Further



www.hikvision.com
support@hikvision.com

