

DS-MDT202 Handheld Terminal



- Android 14 operating system, supports Google GMS server.
- Laser aiming projects a crosshair pattern for easy targeting of objects.
- Self-developed high-performance barcode recognition technology can efficiently read barcodes of various formats.
- Compact appearance design for convenient integration.
- Can quickly identify blurry, distorted, and dirty barcodes.
- Output modes include focus, coverage, broadcast, and clipboard.
- Supports continuous and single scanning modes.
- Scanning interval: 10-2000ms.
- Image Sensor: Front camera: 5 MP; Rear camera: 13 MP.
- Replaceable battery, supports hot swapping, changing battery without power interruption.

▪ Specification

Model		DS-MDT202
Camera	Image Sensor	Front camera: 5 MP; Fix-focus Rear camera: 13 MP; Auto-focus
	Flashing Light	Supported
Screen	Screen Size	5.45 "
	Screen Type	IPS; Capacitive touch panel; multi-touch
	Resolution	720 * 1440 pixel
Storage	CPU	8cores,2.0GHz
	RAM	4 GB
	ROM	64 GB
	Extended Storage	1 TF card (Max. 512 GB)
Wireless Network	Cellular Network	Only available for models with /GLE: GSM: 850/900/1800/1900 WCDMA: B1/2/4/5/8 TD-SCDMA: B34/39 FDD-LTE: B1/2 /3/4/5/7/8/12/17/20/28A/28B TDD-LTE: B34/B38/B39/B40/B41
	Wi-Fi Protocol	802.11 a/b/g/n/ac
	Wi-Fi Frequency Band	2.412~2.472 GHz, 5.15~5.25 GHz, 5.725~5.875 GHz
	Bluetooth	BT 5.0
	Positioning Mode	GPS, BeiDou, Glonass, Galileo
	NFC	Supported
Interface	Button	Side Keys Volume+,Volume-,Left Scan Key, Right Scan Key, Power Button, 1 Reserved Buttons
	SIM Card	Only available for models with /GLE /5G: 2 (Nano-SIM)
	Charging Interface	Waterproof Type C USB interface, supports USB HighSpeed, supports OTG, supports fast charging
General	Operating System	Android 14.0
	Power	Input: AC 100~240V, 50~60Hz Output: DC 5V, 2A
	Client	MDM
	Vibration Motor	Supported
	G-sensor	Supported
	Distance Sensor	Supported
	Light Sensor	Supported
	Drop Specifications	1.5 m



 HikvisionHQ

 Hikvision_Global

 Hikvision Corporate Channel

 hikvisionhq

	Sealing	IP 68
	Operating Condition	Operating Temp: -20 °C to 50 °C Humidity: 95% or less (non-condensing)
	Storage Condition	-40 °C to 70 °C (-40 °F to 158 °F). Humidity 95% or less (non-condensing)
Battery	Battery Type	Lithium-ion battery, replaceable, hot swap
	Capacity	5000 mAh

▪ Available Model

DS-MDT202/4&64/GLE

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq