

CDD15J / CDD15J Li


Electric pallet stacker



Characteristics:

- High power lift pump has high working efficiency.
- Side driving design achieves a smaller steering radius and wide view.
- The driving system with permanent magnetic motor has small volume, light weight and low consumption.
- German water-proof inching switch meets the requirements of harsh working condition such as cold, humidity and dust circumstances.
- Four colors LED electricity meter makes it simple and easy to read.
- External charger has better cooling performance.
- It's more comfortable and easier for operator using a super long handle that integrates with lifting button, key switch, electricity meter, which is suitable for ergonomics; more accurate speed control with turtle speed switch; more durable with high quality air-pressure springs which allows slowly and automatically reset.
- Iron steel protection guard with high density, which is more durable, firm and has high protection effect.
- Maintenance-free battery.

CAPACITY CHART



• CDD15J

CDD15J / CDD15J Li

Manufacturer's Data and Design Characteristics

Characteristics		HELI					
1.1	Manufacturer	HELI					
1.2	Model	CDD15J	CDD15J Li				
1.3	Operation	Pedestrian propelled					
1.4	Rated traction weight	Q (kg)	1500				
1.5	Mast type	Single mast	2-Stage STD				
1.6	Lift	h3 (mm)	1600	2000	2500	3000	3500
1.7	Capacity at highest height	kg	1500	1300	1100	900	750
1.8	Service weight (include battery)	kg	412	460	474	504	526
1.9	Load centre	c (mm)	600				
1.10	Axle centre to fork face	x (mm)	780				
1.11	Wheel base	y (mm)	1225				
1.12	Controller		CURTIS				
Wheels			Polyurethane				
2.1	Wheels type		Polyurethane				
2.2	Driving wheel size	Φ×w(mm)	Φ210×70				
2.3	Bearing wheel size	Φ×w(mm)	Φ80×70				
2.4	Additional wheels (dimensions)	Φ×w(mm)	Φ115×55				
2.5	Wheels, number front/rear (x = driven)		1x+1/4				
Dimensions							
3.1	Height of mast, lowered	h1 (mm)	2014	1495	1745	1995	2245
3.2	Height of mast, extended	h4 (mm)	2014	2452	2952	3452	3952
3.3	Fork Height, Lowered	h13 (mm)	86				
3.4	Overall length	l1 (mm)	1740				
3.5	Length to fork face	l2 (mm)	590				
3.6	Overall width	b1/ b2 (mm)	795				
3.7	Fork dimensions	s/e/l (mm)	60/160/1150				
3.8	Width of forks	b5 (mm)	570/650/695				
3.9	Min. Ground clearance	m2 (mm)	26				
3.10	Aisle width with pallet 1000 x 1200 across forks	Ast (mm)	2245				
3.11	Aisle width with pallet 800 x 1200 along forks	Ast (mm)	2185				
3.12	Min. Turning radius	Wa (mm)	1405				
Performance							
4.1	Travel speed, with/without load	(km/h)	4.0/4.2				
4.2	Lifting speed, with/without load	(mm/s)	92/136				
4.3	Lowering speed, with/without load	(mm/s)	112/98				
4.4	Max. gradeability laden/unladen	(%)	3/10				
4.5	Service brake		Electromagnetic brake				
Drive and Battery							
5.1	Drive motor, output S2 60 min.	(kW)	0.75				
5.2	Lift motor rating at S3 15%	(kW)	2.2				
5.3	Battery according to DIN 43531/35/36 A, B, C, no		no				
5.4	Battery voltage/rated capacity	(V/Ah)	24 / 100		24 / 60 Li		
5.5	Battery weight (± 5%)	(kg)	1 X 40		1 X 40		
Others							
6.1	Noise level at operator's ears	(dB(A))	≤70				
6.2	Steering type		Mechanical steering				

