

8NDL51 16 Ω

Woofer

- 51 mm (2 in) copper voice coil
- 70 - 3000 Hz response
- 94 dB sensitivity
- Neodymium magnet allows a very light yet powerful motor assembly
- Shorting copper cap for extended HF response
- 400 W continuous program power capacity
- Ventilated voice coil gap for reduced power compression



8NDL51 16 Ω

Woofers

SPECIFICATIONS

Nominal Diameter	200 mm (8 in)
Nominal Impedance	16 Ω
Minimum Impedance	12 Ω
Nominal Power Handling	200 W
2 hours test made with continuous pink noise signal within the range Fs-10Fs. Power calculated on rated minimum impedance. Loudspeaker in free air.	
Continuous Power Handling	400 W
Power on Continuous Program is defined as 3 dB greater than the Nominal rating.	
Sensitivity	94 dB
Applied RMS Voltage is set to 4V for 16 ohm Nominal Impedance	
Frequency Range	70 Hz - 3000 Hz
Voice Coil Diameter	51 mm (2 in)
Winding Material	Copper
Former Material	Glass Fibre
Winding Depth	17 mm (0.65 in)
Magnetic Gap Depth	8 mm (0.31 in)
Flux Density	1.05 T
Woofers Cone Treatment	TWP Waterproof Both Sides

PARAMETERS

Thiele-Small parameters are measured after a high level 20 Hz sine wave preconditioning test.

Fs	70 Hz
Re	10.6 Ω
Qes	0.51
Qms	5.88
Qts	0.47
Vas	13.4 dm³ (0.47 ft³)
Sd	220 cm² (34.1 in²)
η ₀	0.9 %
X _{max}	7 mm
X _{var}	7 mm
M _{ms}	26 g
Bl	15.2 Tm
Le	0.6 mH
EBP	137 Hz

DESIGN



Surround Shape	Double Roll
Cone Shape	Exponential
Magnet Material	Neodymium Inside Slug
Spider	Single
Pole Design	Straight Pole
Woofers Cone Treatment	TWP Waterproof Both Sides
Recommended Enclosure	14 dm³ (0.49 ft³)
Recommended Tuning	65 Hz

MOUNTING AND SHIPPING INFO

Overall Diameter	225 mm (8.8 in)
Bolt Circle Diameter	210 mm (8.3 in)
Baffle Cutout Diameter	187 mm (7.4 in)
Depth	90 mm (3.5 in)
Flange and Gasket Thickness	11 mm (0.4 in)
Air Volume Occupied by Driver	1.1 dm³ (0.04 ft³)
Net Weight	1.85 kg (4.08 lb)
Shipping Units	1 pcs
Shipping Weight	2.3 kg (5.07 lb)
Shipping Box	255x255x150 mm (10.04x10.04x5.91 in)


SERVICE KITS

LF recone-kits	RCK008NDL5116
----------------	----------------------





Frequency Response (2,83 Vrms/1 m)



Model: **8 NDL 51**
Enclosure Type: **Bass Reflex**

Internal Net Volume (Liters):	14	Port Area (cm ²):	32,2
Tuning Frequency (Hz):	65	Port Length (cm):	10,8
Frequency (-3 dB) (Hz):	64,7		

Excursion Limited Maximum SPL at 1 meter (dB):	113,4	equal to	160,2 Watts	(Bass Band Power Rating)
Thermal Limited Maximum SPL at 1 meter (dB):	114,4	equal to	200,0 Watts	(Mid Band Power Rating)

8NDL51 16 Ω

Woofer

