

**15HTX100** 8 Ω

- 99 dB (LF), 108.5 dB (MF/HF - DCX354) sensitivity
- 1600 W continuous program power capacity
- 60°x40° nominal coverage
- 52 - 20000 Hz response
- FEA optimized horn flare for improved acoustic loading and controlled coverage
- Double silicone spider with optimized compliance
- Aluminium demodulating ring for very low distortion

We know it's not correct to call the 15HTX100 a tri-axial, but it's one more than a co-axial. A new exponential cone combined with an iteratively optimized 600Hz horn provides the same wide crossover overlap for the low and mid bandpasses as our DCX354 driver offers in the mid and high bandpasses. Unheard of flexibility, point source impact, and controlled off-axis behavior. Ready to drop in to your most daring applications.



# 15HTX100 8 Ω

## GENERAL

|                                            |                                  |
|--------------------------------------------|----------------------------------|
| Nominal Diameter                           | <b>380 mm (15 in)</b>            |
| Frequency Range                            | <b>52 Hz - 20000 Hz</b>          |
| Dispersion Angle                           | <b>60 °</b>                      |
| Horizontal, included by -6 dB down points. |                                  |
| Woofer Cone Treatment                      | <b>TWP Waterproof Both Sides</b> |

## PARAMETERS

Thiele-Small parameters are measured after a high level 20 Hz sine wave preconditioning test.

|      |                                                  |
|------|--------------------------------------------------|
| Fs   | <b>52 Hz</b>                                     |
| Re   | <b>5.5 Ω</b>                                     |
| Qes  | <b>0.305</b>                                     |
| Qms  | <b>5.9</b>                                       |
| Qts  | <b>0.29</b>                                      |
| Vas  | <b>78 dm<sup>3</sup> (2.75 ft<sup>3</sup>)</b>   |
| Sd   | <b>855 cm<sup>2</sup> (132.5 in<sup>2</sup>)</b> |
| η0   | <b>3.5 %</b>                                     |
| Xmax | <b>10 mm (0.4 in)</b>                            |
| Xvar | <b>8.5 mm</b>                                    |
| Mms  | <b>125 g</b>                                     |
| Bl   | <b>27 Tm</b>                                     |
| Le   | <b>0.9 mH</b>                                    |
| EBP  | <b>170 Hz</b>                                    |

## SPECIFICATIONS LF UNIT

|                                                                                                                                                     |                         |
|-----------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| Nominal Impedance                                                                                                                                   | <b>8 Ω</b>              |
| Minimum Impedance                                                                                                                                   | <b>7 Ω</b>              |
| Nominal Power Handling                                                                                                                              | <b>800 W</b>            |
| 2 hours test made with continuous pink noise signal within the range Fs-10Fs. Power calculated on rated minimum impedance. Loudspeaker in free air. |                         |
| Continuous Power Handling                                                                                                                           | <b>1600 W</b>           |
| Power on Continuous Program is defined as 3 dB greater than the Nominal rating.                                                                     |                         |
| Sensitivity                                                                                                                                         | <b>99 dB</b>            |
| Applied RMS Voltage is set to 2.83V                                                                                                                 |                         |
| Frequency Range                                                                                                                                     | <b>52 Hz - 1000 Hz</b>  |
| Voice Coil Diameter                                                                                                                                 | <b>100 mm (4 in)</b>    |
| Winding Material                                                                                                                                    | <b>Aluminium</b>        |
| Former Material                                                                                                                                     | <b>Glass Fibre</b>      |
| Winding Depth                                                                                                                                       | <b>25.1 mm (1 in)</b>   |
| Magnetic Gap Depth                                                                                                                                  | <b>10.2 mm (0.4 in)</b> |
| Flux Density                                                                                                                                        | <b>1.5 T</b>            |

## SPECIFICATIONS MF UNIT

|                                                                                                                                                                      |                          |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| Nominal Impedance                                                                                                                                                    | <b>8 Ω</b>               |
| Minimum Impedance                                                                                                                                                    | <b>7.5 Ω</b>             |
| Nominal Power Handling                                                                                                                                               | <b>90 W</b>              |
| 2 hour test made with continuous pink noise signal within the range from the recommended crossover frequency to 20 kHz. Power calculated on rated minimum impedance. |                          |
| Continuous Power Handling                                                                                                                                            | <b>180 W</b>             |
| Power on Continuous Program is defined as 3 dB greater than the Nominal rating.                                                                                      |                          |
| Sensitivity                                                                                                                                                          | <b>108.5 dB</b>          |
| Applied RMS Voltage is set to 2.83V                                                                                                                                  |                          |
| Frequency Range                                                                                                                                                      | <b>0.5 kHz - 5.5 kHz</b> |
| Recommended Crossover                                                                                                                                                | <b>0.7 kHz</b>           |
| 12 dB/oct. or higher slope high-pass filter.                                                                                                                         |                          |
| Voice Coil Diameter                                                                                                                                                  | <b>76 mm (3 in)</b>      |
| Winding Material                                                                                                                                                     | <b>Aluminium</b>         |
| Inductance                                                                                                                                                           | <b>0.26 mH</b>           |
| Flux Density                                                                                                                                                         | <b>1.9 T</b>             |
| Diaphragm Material                                                                                                                                                   | <b>HT Polymer Ring</b>   |

## SPECIFICATIONS HF UNIT

|                                                                                                                                                                      |                        |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| Nominal Impedance                                                                                                                                                    | <b>8 Ω</b>             |
| Minimum Impedance                                                                                                                                                    | <b>6.5 Ω</b>           |
| Nominal Power Handling                                                                                                                                               | <b>50 W</b>            |
| 2 hour test made with continuous pink noise signal within the range from the recommended crossover frequency to 20 kHz. Power calculated on rated minimum impedance. |                        |
| Continuous Power Handling                                                                                                                                            | <b>100 W</b>           |
| Power on Continuous Program is defined as 3 dB greater than the Nominal rating.                                                                                      |                        |
| Sensitivity                                                                                                                                                          | <b>108.5 dB</b>        |
| Applied RMS Voltage is set to 2.83V                                                                                                                                  |                        |
| Frequency Range                                                                                                                                                      | <b>5 kHz - 20 kHz</b>  |
| Recommended Crossover                                                                                                                                                | <b>4.5 kHz</b>         |
| 12 dB/oct. or higher slope high-pass filter.                                                                                                                         |                        |
| Voice Coil Diameter                                                                                                                                                  | <b>51 mm (2 in)</b>    |
| Winding Material                                                                                                                                                     | <b>Aluminium</b>       |
| Inductance                                                                                                                                                           | <b>0.1 mH</b>          |
| Flux Density                                                                                                                                                         | <b>1.95 T</b>          |
| Diaphragm Material                                                                                                                                                   | <b>HT Polymer Ring</b> |

**15HTX100** 8 Ω**DESIGN**

|                        |                                  |
|------------------------|----------------------------------|
| Surround Shape         | <b>Triple Roll</b>               |
| Cone Shape             | <b>Curvilinear</b>               |
| Magnet Material        | <b>Neodymium Ring</b>            |
| Spider                 | <b>Double Silicone</b>           |
| Pole Design            | <b>T-Pole</b>                    |
| Woofers Cone Treatment | <b>TWP Waterproof Both Sides</b> |
| Recommended Loading    | <b>Vented Box</b>                |
| Cone Material          | <b>Treated Paper</b>             |



**MOUNTING AND SHIPPING INFO**

|                             |                          |
|-----------------------------|--------------------------|
| Overall Diameter            | <b>393 mm (15.5 in)</b>  |
| Bolt Circle Diameter        | <b>372 mm (14.65 in)</b> |
| Baffle Cutout Diameter      | <b>355 mm (14 in)</b>    |
| Depth                       | <b>261 mm (10.28 in)</b> |
| Flange and Gasket Thickness | <b>15 mm (0.6 in)</b>    |
| Net Weight                  | <b>10.8 kg (23.8 lb)</b> |

**SERVICE KITS**


|                          |                     |
|--------------------------|---------------------|
| HF replacement-diaphragm | <b>MMDDCX354HF8</b> |
| MF replacement-diaphragm | <b>MMDDCX354MF8</b> |

# 15HTX100 8 Ω




# 15HTX100 8 Ω

Horizontal Directivity Map



Vertical Directivity Map



**15HTX100** 8 Ω

