

# DE700TN 8 Ω

## SPECIFICATIONS

Driver mounted on B&C ME 90 horn.

|                                                                                                                                                                      |                       |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|
| Throat Diameter                                                                                                                                                      | <b>38 mm (1.5 in)</b> |
| Nominal Impedance                                                                                                                                                    | <b>8 Ω</b>            |
| Minimum Impedance                                                                                                                                                    | <b>8.4 Ω</b>          |
| Nominal Power Handling                                                                                                                                               | <b>110 W</b>          |
| 2 hour test made with continuous pink noise signal within the range from the recommended crossover frequency to 20 kHz. Power calculated on rated minimum impedance. |                       |
| Continuous Power Handling                                                                                                                                            | <b>220 W</b>          |
| Power on Continuous Program is defined as 3 dB greater than the Nominal rating.                                                                                      |                       |
| Sensitivity                                                                                                                                                          | <b>107.5 dB</b>       |
| Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.                                                                                                   |                       |
| Frequency Range                                                                                                                                                      | <b>1 kHz - 18 kHz</b> |
| Recommended Crossover                                                                                                                                                | <b>0.8 kHz</b>        |
| 12 dB/oct. or higher slope high-pass filter.                                                                                                                         |                       |
| Voice Coil Diameter                                                                                                                                                  | <b>75 mm (3 in)</b>   |
| Winding Material                                                                                                                                                     | <b>Aluminium</b>      |
| Inductance                                                                                                                                                           | <b>0.14 mH</b>        |
| Flux Density                                                                                                                                                         | <b>1.9 T</b>          |
| Diaphragm Material                                                                                                                                                   | <b>Titanium</b>       |

## MOUNTING AND SHIPPING INFO

Four M6 holes 90° on 102 mm (4 in) diameter

|                  |                                               |
|------------------|-----------------------------------------------|
| Overall Diameter | <b>180 mm (7.1 in)</b>                        |
| Depth            | <b>70 mm (2.8 in)</b>                         |
| Net Weight       | <b>6 kg (13.2 lb)</b>                         |
| Shipping Units   | <b>1 pcs</b>                                  |
| Shipping Weight  | <b>6.18 kg (13.62 lb)</b>                     |
| Shipping Box     | <b>190x190x100 mm<br/>(7.48x7.48x3.94 in)</b> |



## SERVICE KITS

|                          |                 |
|--------------------------|-----------------|
| HF replacement-diaphragm | <b>MMD3ATN8</b> |
|--------------------------|-----------------|

- 220 W continuous program power capacity
- 1.5" horn throat diameter
- 75 mm (3 in) aluminium voice coil
- Titanium diaphragm
- 500 - 18000 Hz response
- 107.5 dB sensitivity
- Shorting copper cap for extended HF response



**DE700TN 8 Ω**



**DE700TN** 8 Ω

