



SPECIFICATIONS

| | |
|--|----------------|
| Nominal Impedance | 16 Ω |
| Minimum Impedance | 14.0 Ω |
| Nominal Power Handling ¹ | 350 W |
| Continuous Power Handling ² | 700 W |
| Sensitivity ³ | 95.0 dB |
| Frequency Range | 56 - 7000 Hz |
| Voice Coil Diameter | 75 mm (3.0 in) |

DESIGN

| | |
|------------------------|--|
| Surround Shape | Triple roll |
| Cone Shape | Straight |
| Magnet Material | Neo |
| Woofers Cone Treatment | Water,UV repellent |
| Recommended Enclosure | 12.0 dm ³ (0.42 ft ³) |
| Recommended Tuning | 95 Hz |

PARAMETERS⁴

| | |
|---------------------|--|
| Resonance Frequency | 91 Hz |
| Re | 10.2 Ω |
| Qes | 0.39 |
| Qms | 5.9 |
| Qts | 0.37 |
| Vas | 7.3 dm ³ (0.26 ft ³) |
| Sd | 230.0 cm ² (35.65 in ²) |
| Xmax | 6.3 mm |
| Mms | 30.0 g |
| Bl | 21.5 Txm |
| Le | 0.3 mH |
| EBP | 233 Hz |

MOUNTING AND SHIPPING INFO

| | |
|-----------------------------|------------------------------------|
| Overall Diameter | 225 mm (8.86 in) |
| Bolt Circle Diameter | 210 mm (8.27 in) |
| Baffle Cutout Diameter | 186.0 mm (7.32 in) |
| Depth | 105 mm (4.13 in) |
| Flange and Gasket Thickness | 11 mm (0.43 in) |
| Net Weight | 3.5 kg (7.72 lb) |
| Shipping Weight | 4.2 kg (9.26 lb) |
| Shipping Box | 235x235x150 mm (9.25x9.25x5.91 in) |

1. 2 hours test made with continuous pink noise signal within the range F_s-10F_s . Power calculated on rated minimum impedance. Loudspeaker in free air.
2. Power on Continuous Program is defined as 3 dB greater than the Nominal rating.
3. Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.
4. Thiele-Small parameters are measured after a high level 20 Hz sine wave preconditioning test.