

# Smart Dual Water Timer

ATLO-VR2G-BLE-TUYA




1. Meet the Dual Hose Faucet Timer



# Specification:

Bluetooth Range	
Working Water Pressure	7.25-116 psi
Working Temperature	40.1°F-113°F(4.5°C-45°C)
Rain Delay Time	1 day and up to 7 days
Waterproof	IPX5
Battery	

# 2. Meet the Gateway



# Specification:

Working Humidity	10%-90% RH (no condensation)
Range	49.2ft without interference
I	110-250V~50/60Hz

WiFi Frequency	2.4GHz only
Protocol	IEEE 802.11b/g/n & Bluetooth
Total Number Connected	32 MAX
Note	For Indoor Use Only

# 3. Initial Water Timer Setup

- 1 Insert 4x AA Batteries
- Remove the tray on the back of the timer by sliding or pulling it out.
- 2. Insert four AA (1.5V) alkaline batteries and replace the tray.

### • Note:

Please do not mix alkaline, standard (carbon-zinc), or rechargeable batteries.

2 Install the Timer

Connect the timer to an outdoor hose faucet. Your timer is now ready to be used with any product that can be attached to a standard hose faucet.

#### • Note:

Do not place the timer in an underground valve box or anywhere your Bluetooth signal will be obstructed.

### 3 Turn on Your Water

The water must remain on for the timer to work properly.

### 4. Initial Smart Life App Setup

Download the Smart Life App

Scan the QR code and download the free Android or IOS app, then install the APP. If you have already installed the Smart Life APP, go to step 2.







2 Power the Wi-Fi Hub & Timer

Plug the Wi-Fi Hub into an indoor outlet. (The distance between the gateway and the water timer should not exceed 50ft)

4

#### Pair the WI-FI Hub

3

Turn on the phone's bluetooth and WiFi, tap "Add device" or "+" to add the smart device in app. Select "Gateway Control ">"Wireless Gateway(BLE)">add WiFi Hub.



TEnter Password and connect with Wi-Fi. (Only 2.4G Wi-Fi are supported). Waiting for connecting to be 100%. Edit the name of your Hub completed.

Choose an indoor location for your hub near the router and the outside location of your timer and within range of Wi-Fi.Avoid areas where the signal must travel through more thanone wall, dirt, or thick steel barriers.







4 Add the Water timer

After the gateway getting connected, then add the timer on the gateway.

- 4.1) Long-press either of the "On/OFF button" for 6s until the two green lights flash quickly at the same time to keep the time to keep the water timer in pairing mode.
- 4.2) Tap "Add device" to add the timer in Gateway. Select "Add new device".
- 4.3) Waiting for connecting to be 100%. Edit the name of your water timer completed.

# 5. Meet the App Home Screen



# 6. Amazon Alexa and Google Assistant

Smart dual water timer with wifi hub can be used with Alexa and Google Assistant

- If you works with Google Assistant, please follow with the below command.
  - ① Ok, Goolge. start<DEVICENAME>
- ② Ok, Goolge. stop<DEVICENAME>
- 2. If you works with Amazon Alexa, please follow with the below command.
  - 1) Alexa, open <DEVICENAME>
  - ② Alexa, close <DEVICENAME>

#### Note:

- There is a default name of the device(Zone1 / Zone2).
   You can edit the device name by yourself. And if you use the incorrect command, it will not work.
- 2. if you not use WIFI hub, it will not work.

### 7 . Additional Water Timer Features

### 1 Manual Watering

Your timer has the ability to allow you to manually water without disturbing the programmed schedule.

Manual is used to test equipment, run an extra watering cycle in an area, or to use the hose faucet without removing the timer.

Click the button to activate manual watering. Using the app you can click oh 10min to set how long you want manual watering time to run for the "work time", also remaining watering time will be displayed.

### 2 Stop Watering

You can stop the flow of water at any time whether it is during manual watering, or during a programmed time. Click the button once again to stop watering. (NOTE: icon without water droplets)

#### Rain Delay Function

The rain delay function allows you to postpone watering for 1 day and up to 7 days due to rain or when the ground is already wet. Click the button to activate manual watering. Using the app you can click set how long you want the preset rain delay feature.

## 8. Troubleshooting

Q1: Why the Bluetooth water timer didn't turn on/off at preset time?

### A1:

3

- Programming is incorrect
- Water pressure is too low
- Particles of dirt or debris stuck in valve
- More than one start time is programmed with overlapping schedules
- Manual watering is on
- Faulty valve
- The batteries were low
- The faucet is off.

Q2: Why Bluetooth keeps dropping connection?

### A2:

- The Bluetooth of water timer is currently in sleep mode, please wait 5-10 seconds, the device will automatically reconnect. Or scroll down to refresh the home page of the APP, or disconnect the Bluetooth from your phone and turn it on again
- If the device has been connected by other mobile phones, please disconnect first.
- Make sure the device battery is charged and place the phone as close to the device as possible.
- Please note that you don't need to stay connect once you setup your schedule. The device will always keep your watering settings and work automatically according to the schedule.

Q3: Why is the water valve out of little water?

# A3:

If your are gravity feed system such as rain barrel system, then it won't work and will keep low water pressure. Gravity feed has no real pressure when dealing with a rain barrel. It needs pressure measuring.

# 9 . Warm Tips:

- The best range for connection and control is within 49.2ft in the open area.
- The bluetooth water timer does not support Alexa & Google voice or remote control.
- Do not use your timer when the air temperature is below 40°F(4.5°C), the timers should be removed from the hose faucet and stored indoors to avoid potential frozen damage.
- Filter can trap dirt particles, please clean filter regularly and replace if worn.
- Please replace batteries when the low battery indicator appears the display. When replacing the power unit, please make sure that the water timer is dry.
- To prevent leakage, make sure that the water timer is tightly attached to the faucet and hose, add rubber washer and thread seal tape if necessary.

#### • Note:

- (1) The water flow is reduced by half when the two zones are turned on at the same time.
- (2) The water flow in two zones may be different if you turn on one zone first and then turn on the other zone.

12