

Product datasheet

uvex 2 xenova® 9553 1-3

Safety sandal DIN EN ISO 20345:2022 S1 PL FO SR

Sizes: 35 - 52 | Width: 10, 11, 12



AREA OF APPLICATION

Medium applications usually alternate between indoor and outdoor areas, meaning that the demands on the robustness of the outsole of a safety shoe are much higher.

OUTSOLE

Dual-density polyurethane sole



- PU outsole
- shock-absorbing PU midsole with 15% recycled granulate from residues
- antistatic
- short-term heat resistant up to 120°C
- excellent slip resistance (**SR**)
- oil- and fuel resistant (**FO**)
- free of silicones, plasticisers and other substances that interfere with wetting agents



FEATURES	
Upper material	<ul style="list-style-type: none"> • breathable microvelour • suitable for people allergic to chrome • textile distance mesh lining for comfortable foot climate • hook-and-loop fastening • for increased visibility even in dark working environments • soft padding on collar • sizes 35-40 have been produced using a women's last • open upper for increased breathability (clima zone) • removable comfortable insock • metal-free
Lining material	
Fastening	
Reflecting elements	
Comfort	
Insock	
Furthermore	
PROTECTIVE FEATURES	
Toe cap	<ul style="list-style-type: none"> • metal-free protective toe cap • metal-free, textile penetration resistance
Penetration resistance	
CERTIFICATES	
uvex medicare+	<ul style="list-style-type: none"> • certified for orthopaedic insocks and shoe adjustments according to the description in DGUV 112-191 • certified free from animal ingredients and products • additional protection for people with allergies and intolerances • protection against electrostatic charge according to EN 61340-4-3 und EN 61340-5-1
100% vegan	
ESD	
SUSTAINABILITY	
Recycled/sustainable materials	<ul style="list-style-type: none"> • midsole, removable insock and heel cap made wholly or partly from recycled materials • free from harmful substances in accordance with the uvex restricted substances list
ACCESORIES/ SPARE PARTS	
Replacement insock	<ul style="list-style-type: none"> • 9534 7-0 • low 95281 • medium 95282 • high 95283
tune-up insock	