

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 46 (replaces version 45)

Revision: 01.08.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** BIS EPOXY UNIVERSAL BD 24ML*12 L625
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Adhesive
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
UHU GmbH & Co.KG
Herrmannstraße 7
D-77815 Bühl (Baden)
Tel.:0049-(0)7223-284-0
E-mail: sds@boltonadhesives.com
Fax: 0049-(0)7223-284-245
- **Further information obtainable from:** PSRA
- **1.4 Emergency telephone number:**
Emergency medical information: 8am-10pm (seven days) contact
National Poisons Information Centre, Beaumont Hospital, Dublin 9. Tel 01 8092566

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2

H315 Causes skin irritation.

Eye Irrit. 2

H319 Causes serious eye irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



GHS07



GHS09

- **Signal word** Warning

- **Hazard-determining components of labelling:**

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

(Contd. on page 2)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 46 (replaces version 45)

Revision: 01.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

(Contd. of page 1)

táirge imoibriúcháin: roisín eapocsa bisphenol-F- (epichlorhydrin) (meánmheáchan móilíneach ≤ 700)

· **Hazard statements**

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P261 Avoid breathing vapours.
- P280 Wear protective gloves.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P501 Dispose of contents/container in accordance with national regulations.

· **Additional information:**

- EUH205 Contains epoxy constituents. May produce an allergic reaction.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

- **Description:** Adhesive

· **Dangerous components:**

CAS: 1675-54-3 EINECS: 216-823-5 Index number: 603-073-00-2 Reg.nr.: 01-2119456619-26-XXXX	bis-[4-(2,3-epoxipropoxi)phenyl]propane ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	50-100%
EC number: 701-263-0 Reg.nr.: 01-2119454392-40-xxxx	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	≥2.5-<10%
CAS: 25068-38-6	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - <1100) ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205	≥2.5-<10%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 3)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 46 (replaces version 45)

Revision: 01.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

(Contd. of page 2)

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** No special measures required.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Send for recovery or disposal in suitable receptacles.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** No special measures required.

(Contd. on page 4)

**Safety data sheet**

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 46 (replaces version 45)

Revision: 01.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 10
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs****1675-54-3 bis-[4-(2,3-epoxipropoxi)phenyl]propane**

Oral	Consumer, oral, longterm exposition	0.5 mg/kg bw/day (rat)
Dermal	Worker, dermal, longterm exposition	0.75 mg/kg bw/day (rat)
	Consumer, dermal, longterm exposition	0.0893 mg/kg bw/day (rat)
Inhalative	Worker, inhalative, longterm exposition	4.93 mg/m ³ (rat)
	Consumer, inhalative, longterm exposition	0.87 mg/m ³ (rat)

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Oral	Consumer, oral, longterm exposition	6.25 mg/kg bw/day
Dermal	Worker, dermal, longterm exposition	104.15 mg/kg bw/day
	Consumer, dermal, longterm exposition	62.5 mg/kg bw/day
Inhalative	Worker, inhalative, longterm exposition	29.39 mg/m ³
	Consumer, inhalative, longterm exposition	8.7 mg/m ³

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - <1100)

Oral	Consumer, oral, longterm exposition	0.5 mg/kg bw/day (rat)
Dermal	Worker, dermal, longterm exposition	0.75 mg/kg bw/day (rat)
	Consumer, dermal, longterm exposition	0.0893 mg/kg bw/day (rat)
Inhalative	Worker, inhalative, longterm exposition	4.93 mg/m ³ (rat)
	Consumer, inhalative, longterm exposition	0.87 mg/m ³ (rat)

· **PNECs****1675-54-3 bis-[4-(2,3-epoxipropoxi)phenyl]propane**

Oral	Secondary Poisoning	11 mg/kg (rat)
	Fresh water	0.006 mg/l (rat)
	Fresh water sediment	0.341 mg/kg dry weight (rat)
	Marine water	0.001 mg/l (rat)
	Marine sediment	0.034 mg/kg dry weight (rat)
	Soil	0.065 mg/kg (rat)

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 46 (replaces version 45)

Revision: 01.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

(Contd. of page 4)

Sewage treatment plant	10 mg/l (rat)
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	
Fresh water	0.003 mg/l
Fresh water sediment	0.294 mg/kg dry weight
Marine water	0 mg/l
Marine sediment	0.0294 mg/kg dry weight
Soil	0.237 mg/kg

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Not required.

· **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Recommended thickness of the material: > 0,12 mm

glove material for short-term use / splash: (10 min <BTT <480 min): nitrile rubber, neoprene rubber
Nitrile rubber, NBR

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

· **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· **Eye/face protection**



Tightly sealed goggles

(Contd. on page 6)



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 46 (replaces version 45)

Revision: 01.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

Goggles recommended during refilling

(Contd. of page 5)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state	Fluid
· Colour:	Colourless
· Odour:	Weak, characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	Undetermined.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	>150 °C
· Decomposition temperature:	Not determined.
· pH at 20 °C	6
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	40000 mPas
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	1.15 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information

All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

· Appearance:

· Form: Fluid

· Important information on protection of health and environment, and on safety.

· Ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

· Solvent content:

· Solids content: 91.0 %

· Change in condition

· Evaporation rate: Not determined.

(Contd. on page 7)

IE

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 46 (replaces version 45)

Revision: 01.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

(Contd. of page 6)

· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1675-54-3 bis-[4-(2,3-epoxypropoxy)phenyl]propane

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

- **Skin corrosion/irritation**
Causes skin irritation.

(Contd. on page 8)



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 46 (replaces version 45)

Revision: 01.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

(Contd. of page 7)

- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity**
Not applicable.
Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable.
- **Sensitisation** Not applicable.
- **Repeated dose toxicity** Not applicable.
- **11.2 Information on other hazards**

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

(Contd. on page 9)

IE

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 46 (replaces version 45)

Revision: 01.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

(Contd. of page 8)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR/ADN, IMDG, IATA**

UN3082

- **14.2 UN proper shipping name**
- **ADR/ADN**

3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), táirge imoibriúcháin: roisín eapocsa bisphenol-F-(epichlorhydrin) (meánmheáchan móilíneach ≤ 700))

- **IMDG**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)), MARINE POLLUTANT

- **IATA**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))

- **14.3 Transport hazard class(es)**

- **ADR/ADN**



- **Class**

9 (M6) Miscellaneous dangerous substances and articles.

- **Label**

9

- **IMDG, IATA**



- **Class**

9 Miscellaneous dangerous substances and articles.

(Contd. on page 10)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 46 (replaces version 45)

Revision: 01.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

(Contd. of page 9)

· Label	9
· 14.4 Packing group · ADR/ADN, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR/ADN): · Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR/ADN · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code	3 (-)
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN); EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700), TÁIRGE IMOIBRIÚCHÁIN: ROISÍN EAPOCSA BISPHENOL-F- (EPICHLORHYDRIN) (MEÁNMHÉACHAN MÓILÍNEACH ≤ 700)), 9, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category E2 Hazardous to the Aquatic Environment

(Contd. on page 11)

**Safety data sheet**

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 46 (replaces version 45)

Revision: 01.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

(Contd. of page 10)

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**

- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

- **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.
- EUH205 Contains epoxy constituents. May produce an allergic reaction.

- **Classification according to Regulation (EC) No 1272/2008**

Skin corrosion/irritation Serious eye damage/irritation Skin sensitisation Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
---	--

- **Department issuing SDS:** PSRA
- **Contact:** PSRA
- **Date of previous version:** 18.05.2021
- **Version number of previous version:** 45
- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 12)



Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 46 (replaces version 45)

Revision: 01.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

(Contd. of page 11)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

IE

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 33 (replaces version 32)

Revision: 13.08.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier**Trade name:** BIS EPOXY UNIVERSAL BD 24ML*12 L625**1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

Application of the substance / the mixture Adhesive**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

UHU GmbH & Co.KG

Herrmannstraße 7

D-77815 Bühl (Baden)

Tel.:0049-(0)7223-284-0

E-mail: sds@boltonadhesives.com

Fax: 0049-(0)7223-284-245

Further information obtainable from: PSRA**1.4 Emergency telephone number:**

Emergency medical information: 8am-10pm (seven days) contact

National Poisons Information Centre, Beaumont Hospital, Dublin 9. Tel 01 8092566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture**Classification according to Regulation (EC) No 1272/2008**

GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS05

GHS07

GHS09

Signal word Danger

(Contd. on page 2)

IE

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 33 (replaces version 32)

Revision: 13.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

(Contd. of page 1)

· **Hazard-determining components of labelling:**

Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine

Amines, polyethylenepoly-, tetraethylenepentamine fraction

· **Hazard statements**

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing vapours.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with national regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Adhesive

· **Dangerous components:**

Polymer Reg.nr.: 01-2119972322-40-XXXX	Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine ⚠ Eye Dam. 1, H318; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	50-100%
CAS: 68154-62-1 EC number: 614-339-2	Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	25-50%
CAS: 90640-66-7 EINECS: 292-587-7 Reg.nr.: 01-2119487290-37-XXXX	Amines, polyethylenepoly-, tetraethylenepentamine fraction ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H312; Skin Sens. 1, H317	≥3-<5%
CAS: 90640-67-8 EINECS: 292-588-2 Reg.nr.: 01-2119487919-13-XXXX	Amines, polyethylenepoly-, triethylenetetramine fraction ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 3)



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 33 (replaces version 32)

Revision: 13.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

(Contd. of page 2)

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** No special measures required.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Send for recovery or disposal in suitable receptacles.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

(Contd. on page 4)

IE

**Safety data sheet**

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 33 (replaces version 32)

Revision: 13.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

(Contd. of page 3)

- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 10
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs****90640-66-7 Amines, polyethylenepoly-, tetraethylenepentamine fraction**

Oral	Consumer, oral, longterm exposition	0.21 mg/kg bw/day
Dermal	Worker, dermal, longterm exposition	0.25 mg/kg bw/day
	Consumer, dermal, longterm exposition	0.021 mg/kg bw/day
Inhalative	Worker, inhalative, longterm exposition	0.82 mg/m ³
	Consumer, inhalative, longterm exposition	0.14 mg/m ³

90640-67-8 Amines, polyethylenepoly-, triethylenetetramine fraction

Oral	Consumer, oral, longterm exposition	14 mg/kg bw/day (rat)
Inhalative	Worker, inhalative, longterm exposition	0.54 mg/m ³ (rat)
	Consumer, inhalative, longterm exposition	0.096 mg/m ³ (rat)

· **PNECs****90640-66-7 Amines, polyethylenepoly-, tetraethylenepentamine fraction**

Fresh water	0.01 mg/l
Fresh water sediment	3.198 mg/kg dry weight
Marine water	0.001 mg/l
Marine sediment	0.32 mg/kg dry weight
Soil	2.5 mg/kg
Sewage treatment plant	4.6 mg/l

90640-67-8 Amines, polyethylenepoly-, triethylenetetramine fraction

Fresh water	0.027 mg/l (rat)
Fresh water sediment	8.572 mg/kg dry weight (rat)
Marine water	0.003 mg/l (rat)
Marine sediment	0.857 mg/kg dry weight (rat)
Soil	1.25 mg/kg (rat)
Sewage treatment plant	0.13 mg/l (rat)

- **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 33 (replaces version 32)

Revision: 13.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

(Contd. of page 4)

- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Respiratory protection:** Not required.
- **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
Recommended thickness of the material: > 0,12 mm
glove material for short-term use / splash: (10 min <BTT <480 min): nitrile rubber, neoprene rubber
Nitrile rubber, NBR
- **Penetration time of glove material**
For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes
(Permeation according to EN 374 Part 3: Level 1).
- **Eye/face protection**



Tightly sealed goggles

Goggles recommended during refilling

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Fluid
- **Colour:** According to product specification
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** Undetermined.
- **Boiling point or initial boiling point and boiling range** Undetermined.
- **Flammability** Not applicable.

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 33 (replaces version 32)

Revision: 13.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

(Contd. of page 5)

<ul style="list-style-type: none"> · Lower and upper explosion limit · Lower: · Upper: · Flash point: · Decomposition temperature: · pH · Viscosity: · Kinematic viscosity · Dynamic at 20 °C: · Solubility · water: · Partition coefficient n-octanol/water (log value) · Vapour pressure: · Density and/or relative density · Density at 20 °C: · Relative density · Vapour density 	<p>Not determined.</p> <p>Not determined.</p> <p>>150 °C</p> <p>Not determined.</p> <p>Not determined.</p> <p>Not determined.</p> <p>Not determined.</p> <p>27500 mPas</p> <p>Not miscible or difficult to mix.</p> <p>Not determined.</p> <p>Not determined.</p> <p>0.97 g/cm³</p> <p>Not determined.</p> <p>Not determined.</p>
<ul style="list-style-type: none"> · 9.2 Other information · Appearance: · Form: · Important information on protection of health and environment, and on safety. · Ignition temperature: · Explosive properties: · Solvent content: · Solids content: · Change in condition · Evaporation rate 	<p>All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.</p> <p>Fluid</p> <p>Product is not selfigniting.</p> <p>Product does not present an explosion hazard.</p> <p>100.0 %</p> <p>Not determined.</p>
<ul style="list-style-type: none"> · Information with regard to physical hazard classes · Explosives · Flammable gases · Aerosols · Oxidising gases · Gases under pressure · Flammable liquids · Flammable solids · Self-reactive substances and mixtures · Pyrophoric liquids · Pyrophoric solids · Self-heating substances and mixtures · Substances and mixtures, which emit flammable gases in contact with water · Oxidising liquids · Oxidising solids 	<p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p>

(Contd. on page 7)

IE

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 33 (replaces version 32)

Revision: 13.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

(Contd. of page 6)

· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

90640-66-7 Amines, polyethylenepoly-, tetraethylenepentamine fraction

Oral	LD50	3221 mg/kg (rat)
------	------	------------------

Dermal	LD50	1260 mg/kg (rat)
--------	------	------------------

90640-67-8 Amines, polyethylenepoly-, triethylenetetramine fraction

Oral	LD50	1716.2 mg/kg (rat)
------	------	--------------------

Dermal	LD50	1465.4 mg/kg (rabbit)
--------	------	-----------------------

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity**
Not applicable.
Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable.
- **Sensitisation** Not applicable.
- **Repeated dose toxicity** Not applicable.

(Contd. on page 8)



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 33 (replaces version 32)

Revision: 13.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

(Contd. of page 7)

11.2 Information on other hazards**Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information**12.1 Toxicity****Aquatic toxicity:** No further relevant information available.**12.2 Persistence and degradability** No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects**Remark:** Toxic for fish**Additional ecological information:****General notes:**

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information****14.1 UN number or ID number****ADR/ADN, IMDG, IATA**

UN3082

(Contd. on page 9)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 33 (replaces version 32)



Revision: 13.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

(Contd. of page 8)



<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR/ADN · IMDG, IATA 	<p>3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Amines, polyethylenepoly-, tetraethylenepentamine fraction)</p>
--	--

<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR/ADN 	<p>9 (M6) Miscellaneous dangerous substances and articles.</p>
--	--

<ul style="list-style-type: none"> · Class · Label 	<p>9</p>
--	----------

<ul style="list-style-type: none"> · IMDG, IATA 	<p>9 Miscellaneous dangerous substances and articles.</p>
---	---

<ul style="list-style-type: none"> · Class · Label 	<p>9</p>
--	----------

<ul style="list-style-type: none"> · 14.4 Packing group · ADR/ADN, IMDG, IATA 	<p>III</p>
---	------------

<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR/ADN): · Special marking (IATA): 	<p>Product contains environmentally hazardous substances: Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)</p>
---	--

<ul style="list-style-type: none"> · 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category 	<p>Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F A</p>
---	---

<ul style="list-style-type: none"> · 14.7 Maritime transport in bulk according to IMO instruments 	<p>Not applicable.</p>
---	------------------------

<ul style="list-style-type: none"> · Transport/Additional information: · Quantity limitations 	<p>On passenger aircraft/rail: 450 L On cargo aircraft only: 450 L</p>
---	--

(Contd. on page 10)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 33 (replaces version 32)

Revision: 13.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

(Contd. of page 9)

<ul style="list-style-type: none"> · ADR/ADN · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code 	<p>5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p> <p>3 (-)</p>
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	<p>5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p>
<ul style="list-style-type: none"> · UN "Model Regulation": 	<p>UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. 9, III</p>

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category E2** Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**

- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

- **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Contd. on page 11)



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024

Version number 33 (replaces version 32)

Revision: 13.08.2024

Trade name: BIS EPOXY UNIVERSAL BD 24ML*12 L625

(Contd. of page 10)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

Serious eye damage/irritation Skin sensitisation Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
--	--

· Department issuing SDS: PSRA

· **Contact:** PSRA

· **Date of previous version:** 18.05.2021

· **Version number of previous version:** 32

· Abbreviations and acronyms:

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Corr. 1B: Skin corrosion/irritation – Category 1B
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

IE