



photo OHI 25-60/130



photo OHI 25-40/180



photo OHI 32-80/180

OHI

The pumps are equipped with 3-gear motors, allowing to adjust the operating parameters to the user's needs.

The pumps are available in two body versions: bronze or cast iron. Due to structure and high quality of applied materials, the pumps are very quiet. All OHI pumps have the PZH attestation.



photo pipe unions OHI

PARAMETERS

Name	Gear	Head (m)	Flow (l/min)	Motor power (W)	Diameter/pipe union (inches)	Port distribution (mm)
OHI 15-60/130	1	3	22	46	1 x ¾	130
	2	5	38	63		
	3	6	55	93		
OHI 25-40/130	1	3	18	38	1 x ¾	130
	2	4	36	53		
	3	4,5	48	71		
OHI 25-40/180	1	3	18	38	1½ x 1	180
	2	4	36	53		
	3	4,5	48	71		
OHI 25-60/130 OHI 25-60/180	1	3	22	46	1½ x 1	130 180
	2	5	38	63		
	3	6	55	93		
OHI 25-80/180	1	6,5	43	150	1½ x 1	130
	2	7,5	103	220		
	3	8	160	270		
OHI 32-60/180	1	3	22	46	2 x 1¼	180
	2	5	38	63		
	3	6	55	93		
OHI 32-80/180	1	6,5	43	150	2 x 1¼	180
	2	7,5	103	220		
	3	8	160	270		