

# DTP790 BATTERY TESTER



- Digital tester with LCD backlit display and built-in printer.
- For 4-250Ah batteries at 12V.
- Tests carried out: battery status, cranking efficiency, of the cranking system and the alternator circuit.

## DESCRIPTION

Digital tester to check the status of the battery, the starting efficiency (CCA), the starter system and the alternator circuit of the vehicle.

Selectable reference international standards for vehicles to which the various starting amp ranges used by the battery manufacturer correspond.

Practical and compact, it allows operation on 12V batteries (WET, GEL, MF, AGM, PbCa, EFB) both disconnected and connected to the vehicle, facilitating testing operations which are rapid and easy to carry out.










The backlit LCD screen facilitates data reading, even in poorly lit environments.

Equipped with a built-in printer to print reports.

Features:

- for WET, GEL, MF, AGM, PbCa, EFB batteries from 4-250 Ah at 12V;
- tests carried out: battery status, starting efficiency (CCA), starting system, alternator circuit of the vehicle;
- selectable reference standard for the vehicle;
- tests can be carried out with battery disconnected or connected to the vehicle;
- backlit LCD display;
- multilingual: EN, IT, FR, DE, ES, NL;
- direct printing of reports using built-in printer.

## TECHNICAL DATA

<b>CODE</b>	CODE 804245		Battery voltage 12 V		Battery range 4-250 Ah
	Starting current range EN 100/2000-EN-SAE-CCA-BCI A		Starting current range IEC 100/1400-IEC-DIN A		Starting cur.range CA(MCA) 100/2000-CA(MCA) A
	Starting current range JIS 26A17/245H2-JIS A		Operating temper.(min-max) 0 - 40 °C		DIMENSIONS 9,8 x 7,8 x 27,5 cm
	WEIGHT 0,714 kg				

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL