

400V steel dent puller with 3800A output current, ideal for all steel straightening and dent pulling jobs.

Quite efficient thanks to 2 guns, one automatic and one with trigger, and its user friendly control panel.

SIMPLE TO USE

Only 2 parameters to select :

- the output power level (amongst 11 levels)
 - the tool which is used (amongst 7 tools)
- => no need to select the welding current and welding time.**

Manual triggering

The welding occurs when pressing the trigger when the tool is in contact with the part to straighten.

Automatic triggering

The welding is triggered automatically by a simple contact between the tool and the part to straighten.

Cables length

Power supply: 8 m

Earth: 2 m

Gun: 2 m + 3 m



DELIVERED AS A STANDARD WITH:

- Earth cable 70 mm² (2m long cable)
- 2 multi functional guns (connector) :
 - inertia hammer with star
 - welding of studs, rivets and rings
 - contact shrinking, graphite pen.
- 8 m long mains supply cable
- an accessories box with consumables

OPTION: Manuspot Ref: 050679



Levelling bar
Ref: 050693



4 hooks claw
Ref: 049758

Chariot Trolley
Spot 800
Ref: 051331



Quick spot air gun V2
Ref: 057340



	I ₂ max A		U ₂ V		I _{RMS} A			SYNERGIC			
50/60hz									cm	kg	
400 V	3800	Manuel Auto	7,4	16	2800	OK	OK	•	22.5x36x23.5	25.5	