

Specifications

		400 A	600 A
Current AC	Range	40 - 400 A	40 - 600 A
	Accuracy	$\pm 2.5\% + 5d$	
Current DC	Range	40 - 400 A	40 - 600 A
	Accuracy	$\pm 2.0\% + 3d$	
Voltage AC	Range	4 - 600 V	4 - 600 V
	Accuracy	$\pm 1.0\% + 5d$	
Voltage DC	Range	400 mV - 600 V	
	Accuracy	$\pm 0.8\% + 1d$	
Resistance	Range	400 Ω - 40 M Ω	
	Accuracy	$\pm 1.0\% + 2d$	
Frequency		10Hz to 10MHz	
Storage temperature		-40 ~ +60 °C	
Ø max. of the clamp		28 mm	
Screen size		35.6 x 18 mm	
Battery		9 V	
Battery life		150 h	
Dimensions		208 x 76 x 30 mm	
Weight		260 g	

GENERATOR CONTROL

► Ref : 053991 (400A)
► Ref : 053984 (600A)

400A & 600A CLAMP METER



- + Slim and ergonomic.
- + Measuring AC / DC current up to 600 A.
- + Measuring resistance up to 40 M Ω with continuity buzzer.
- + Wide opening jaw.
- + Data hold.
- + Low battery display.
- + Carry bag.



DESCRIPTION

This professional clamp meter is capable of measuring AC and DC current and offers high quality functions. It can measure voltage up to 600V and test the resistance, the frequency and duty cycle. The compact dimensions of this clamp enable use in difficult to access areas.