

MTF 3000



MTF 3000



duolift®

LIFTS

SOLLEVATORE ELETTROMECCANICO A DOPPIA COLONNA

- Massima altezza di sollevamento 2030 mm
- Esecuzione asimmetrica e dei bracci per un accesso al veicolo agevolato
- Speciale configurazione dei bracci e dei tamponi in modo da sollevare un'ampia gamma di veicoli senza l'ausilio di accessori opzionali
- Facile posizionamento di veicoli a profilo ribassato grazie ai 98 mm di altezza di sollevamento mini.
- Arresto automatico dei bracci
- Lubrificazione automatica degli alberi di sollevamento e dei dadi di sicurezza
- Dado di sollevamento in materiale Nylatron

ELECTRO-MECHANICAL TWO POST LIFT

- Max lifting height: 2030 mm
- Asymmetric design of arms for an easier access to vehicle
- Special arms and pads configuration to fit a wide range of vehicles without using additional accessories
- Easy accommodation of low-bed cars due to 98 mm minimum pick-up height
- Automatic locking of arms
- Lifting nuts made of wear-proof material (Nylatron®)
- Automatic lubrication of lifting screws and safety nuts

PONT ÉLEVATEUR 2 COLONNES ÉLECTROMÉCANIQUE

- Hauteur maximum de levée 2030mm
- Colonnes asymétriques facilitant l'ouverture des portes du véhicule
- Configuration des bras et tampons permettant la levée des véhicules TOURISME/VUL sans accessoire optionnel
- Accès aisé des véhicules surbaissés ou avec spoiler (faible garde au sol) grâce à l'hauteur mini de 98 mm
- Blocage automatique des bras
- Ecrou porteur silencieux et résistant à l'usure (en nylatron)
- Graissage automatique des vis porteuses et écrous de sécurité



SPECIFICHE TECNICHE	SPECIFICATIONS	CARACTERISTIQUES TECHNIQUES	
Capacità di carico max	Capacity	Portée	3000 kg (6600 lbs)
Tempo di sollevamento	Lifting time	Temps de levage	45 sec
Altezza di sollevamento maxi.	Max lifting height	Hauteur de levage maxi	2030 mm (80")
Motore di azionamento	Drive motor	Moteur	2 x 230 / 400 V1, 8kW 3ph 50 Hz
Pesi di spedizione	Shipping weight	Poids livraison	650 kg (1430 lbs)
Dimensioni imballo	Packaging dimensions	Encombrement livraison	330 x 82 x 70 cm (130" x 32" x 27")

EMEA-JA
Snap-on Equipment s.r.l. - Via Prov. Carpi, 33 - 42015 Correggio (RE)
Phone: +39 0522 733-411 - Fax: +39 0522 733-479 - www.hofmann-europe.com

Austria
Snap-on Equipment Austria GmbH - Hauptstrasse 24/Top 14 - A-2880 St. Corona/Wechsel (RE)
Phone: +43 1 865 97 84 - Fax: +43 1 865 97 84 29 - www.hofmann-europe.com

France
Snap-on Equipment France - ZA du Vert Galant - 15, rue de la Guivernone BP 97175
Saint-Ouen-l'Aumône - 95056 Cergy-Pontoise CEDEX
Phone: +33 134 48 58-78 - Fax: +33 134 48 58-70 - www.hofmann-france.fr

Germany
Snap-on Equipment GmbH - Konrad-Zuse-Straße 1 - 84579 Unterneukirchen
Phone: +49 8634 622-0 - Fax: +49 8634 5501 - www.hofmann-deutschland.com

Italy
Snap-on Equipment s.r.l. - Via Prov. Carpi, 33 - 42015 Correggio (RE)
Phone: +39 0522 733-411 - Fax: +39 0522 733-410 - www.hofmann-italia.com

United Kingdom
Snap-on Equipment Ltd. - Unit 17 Denney Road, King's Lynn - Norfolk PE30 4HG
Phone: +44 118 929-6811 - Fax: +44 118 966-4369 - www.snapon-equipment.co.uk



Part of the machines is illustrated with optional extras which are available at extra cost. Technical and visual modifications reserved.

Cod.: 9702 153 - 12/2016

HOFMANN