

NITRO@SERVICE
LINE

Corredo standard / Standard outfits



IT GENERATORI DI AZOTO CON SISTEMA A MEMBRANA PERMEABILE PER IL GONFIAGGIO DI PNEUMATICI DI AUTO, CAMION E AUTOBUS

- > Purezza minima: 95%
- > Filtri disoleatori e a carboni attivi interni
- > **A:** Strumento di controllo visivo intasamento filtri
- > Scaricatore automatico di condensa
- > Deviatore aria-azoto
- > Manometro controllo pressione azoto in uscita
- > Uscita supplementare per serbatoio esterno
- > **Serbatoio da 90 kg incluso (modelli Nitro@service 1200/3600)**
- > **Con carrello: due ruote fisse e due girevoli**
- > **B:** Pistola di gonfiaggio/sgonfiaggio Michelin con venturimetro e tubo spiralato 8 mt
- > **C:** 20 tappi per azoto per pneumatici gonfiati ad azoto

EN NITROGEN GENERATORS WITH PERMEABLE MEMBRANE SYSTEM FOR INFLATING TYRES OF CARS, VANS AND BUSES

- > Minimum purity: 95%
- > Built-in, oil separating and active carbon filters
- > **A:** Filter blockage check instrument
- > Automatic condensation overflow
- > Air-nitrogen switch
- > Nitrogen outlet pressure gauge
- > Extra outlet for external tank
- > **90 lt tank included (by Nitro@service 1200 / 3600)**
- > **With trolley: 2 fixed wheels and 2 rotating wheels**
- > **B:** Inflating/deflating Michelin gun with Venturi meter and 8 mt spiral hose
- > **C:** 20 caps for tyres inflated with nitrogen

Accessori a richiesta / Optional Accessories

Cod. 03.000.14

- > Tappi per azoto per pneumatici gonfiati ad azoto. Confezione 100pz.
- > Kit of caps for tyres inflated with nitrogen, 100pcs.

Cod. 03.006.01

- > Kit filtri di ricambio per Nitroservice 12000/24000, 3pz.
- > Kit of spare cartridges for Nitroservice 12000/24000, 3pcs.

Cod. 03.006.02

- > Kit filtri di ricambio per Nitroservice 1200 / 3600, 2pz.
- > Kit of spare cartridges for Nitroservice 1200 / 3600, 2pcs

Importante: specificare il numero di serie al momento dell'ordine
Important: please specify the serial number in the order

NITRO@SERVICE LINE	NITRO@SERVICE 1200 Cod. 03.002.40	NITRO@SERVICE 3600 Cod. 03.002.41	NITRO@SERVICE 12000 Cod. 03.002.42	NITRO@SERVICE 24000 Cod. 03.002.43
Capacità flusso / flow capacity	1,2 Nm³/h 10 bar (145 PSI)	3,6 Nm³/h 10 bar (145 PSI)	12 Nm³/h 10 bar (181 PSI)	24 Nm³/h 10 bar (181 PSI)
Purezza / purity	Min. 95%	Min. 95%	Min. 95%	Min. 95%
Serbatoio interno / Internal tank	90 lt (Nitro@service)	90 lt (Nitro@service)	Può lavorare senza serbatoio esterno Can work without external tank	Può lavorare senza serbatoio esterno Can work without external tank
Dimensioni / Dimensions	60 x 44 x 132 cm	60 x 44 x 132 cm	60 x 44 x 132 cm	60 x 44 x 132 cm
Peso / Weight	75 kg	75 kg	65 kg	70 kg