

## OTL150 grey 1xAl/Cu 25-150mm<sup>2</sup> 1500V Universal terminal

|                                       |                                                                    |
|---------------------------------------|--------------------------------------------------------------------|
| SKU                                   | MAA1150A10                                                         |
| EAN                                   | 4744397013941                                                      |
| Color                                 | Grey                                                               |
| Wire material                         | Al/Cu                                                              |
| Cross-section min. (mm <sup>2</sup> ) | 25                                                                 |
| Cross-section max. (mm <sup>2</sup> ) | 150                                                                |
| Input wire min. (mm <sup>2</sup> )    | 25                                                                 |
| Input wire max. (mm <sup>2</sup> )    | 150                                                                |
| Output wire min. (mm <sup>2</sup> )   | 25                                                                 |
| Output wire max. (mm <sup>2</sup> )   | 150                                                                |
| Number of connections                 | 2                                                                  |
| Nominal current (A)                   | 320 (Cu) / 290 (Al)                                                |
| Nominal voltage (V)                   | 1000 AC / 1500 DC                                                  |
| Service temperature (°C)              | 80                                                                 |
| Material                              | Tin-plated aluminium, polyamide PA66                               |
| Mounting method                       | DIN rail, screw                                                    |
| Item width (mm)                       | 31                                                                 |
| Item length (mm)                      | 84                                                                 |
| Item height (mm)                      | 54                                                                 |
| Item weight (g)                       | 100                                                                |
| Screw                                 | Hex 6                                                              |
| Tightening torque (Nm)                | 14 Nm (25 - 50 mm <sup>2</sup> ) 35 Nm (70 - 150 mm <sup>2</sup> ) |
| IP rating                             | IP20                                                               |
| Certification                         | EN 61238-1; EN60947-7-1                                            |



|                               |          |
|-------------------------------|----------|
| <b>Flame resistance</b>       | UL94 V0  |
| <b>CN8 code</b>               | 85369010 |
| <b>Package quantity (pcs)</b> | 20       |