

OJL280A in 1xAl/Cu120 out 2x35/5x16/ 4x10mm² Distribution block

SKU	MAB1281S10
EAN	4744397014450
Color	Grey
Wire material	Al/Cu
Cross-section min. (mm ²)	2,5
Cross-section max. (mm ²)	120
Input wire min. (mm ²)	1 x 35
Input wire max. (mm ²)	1 x 120
Output wire min. (mm ²)	9 x 2,5 / 2 x 6
Output wire max. (mm ²)	4 x 10 / 5 x 16 / 2 x 35
Number of connections	12
Nominal current (A)	280 (Cu) / 250 (Al)
Nominal voltage (V)	1000
Service temperature (°C)	80
Material	Tin-plated aluminium, polyamide PA66
Mounting method	DIN rail, screw
Item width (mm)	44,4
Item length (mm)	97
Item height (mm)	51
Item weight (g)	178
Screw	Hex 3 / 4 / 6
Tightening torque (Nm)	3 Nm (2,5 - 16 mm ²) 6 Nm (25 - 35 mm ²) 10 Nm (50 - 70 mm ²) 19 Nm (95 - 120 mm ²)
IP rating	IP20



Certification	EN 61238-1:2003; EN 60947-7-1:2014
CN8 code	85369001
Package quantity (pcs)	12