

*ETITEC V T2 255/20 3+1



Specifications

ETI Code	002442957
Description	*ETITEC V T2 255/20 3+1
Class name	Surge arrester
Type	T2
AC max continuous operating voltage Uc	255V
In 8/20 (kA)	20kA
Max. discharge current I _{max} , 8/20 (kA)	40kA
Up - Voltage protection level (kV)	1.5kV
Leakage current	NO
Applied technology	MOV,GDT
Remote signalisation	NO
Network system	TT/TN-S
Number of modules	4
Built-in depth (mm)	68mm
function	SPD
Catalogue Group	ETITEC V
Max. back-up fuse for short circuit protection	A

Online product page 

Other documentation



Technical data catalogue

3D Model

2D File

Instruction manual

CE declaration

Eplan file

ETIM international clasification

Classification	EC000941
Class name	Surge protection device for power supply systems
System configuration DC	No
System configuration IT	No
System configuration TN-C	No
System configuration TN-S	Yes
System configuration TT	Yes
System configuration other	No
Nominal discharge surge current (8/20)	20kA
Nominal voltage AC	230V
Short-circuit breaking capacity (I _{sc})	25kA
Max. continuous voltage AC	255V
Max. discharge surge current (8/20)	40kA
Mounting method	DIN rail (top hat rail) 35 mm
Max. conductor cross section solid (solid, stranded)	35mm ²
Max. conductor cross section flexible (fine-strand)	25mm ²
With remote signalling contact	No
Integrated backup fuse	No
Signalling at the device	Optical
Category type 2	Yes
Degree of protection (IP)	IP20

Dimension drawing

