

R 63-40 230V



Specifications

ETI Code	002463450
Description	R 63-40 230V
Class name	Modular contactor
Rated operational current Ie AC-1/AC-7 (A)	63A
Rated operational voltage AC (V)	440V
Rated AC control circuit voltage Uc (V)	230V
Type	AC
Rated Frequency (Hz)	50Hz/60Hz
Number of NO contacts	4
function	Modular contactor
Mounting type	DIN rail
Catalogue Group	R

Online product page [🔗](#)

Other documentation



3D Model

2D File

CE declaration

Eplan file

ETIM international clasification

Classification	EC001653
Class name	Installation contactor for distribution board
Rated operating voltage	230...400V
Rated operation current	63A
Rated excitation voltage	230...230V
Voltage type (operating voltage)	AC
Voltage type (excitation voltage)	AC
Number of contacts as normally open contact	4
Max. incandescent lamp load	8000W
Max. load fluorescent lamp	5100VA
Max. load fluorescent lamp (Duo circuit)	8120VA
Max. load fluorescent lamp (parallel compensated)	3740VA
Slider for hand switch	No
Number of modular spacings	3
Built-in depth	60mm
Additional equipment possible	Yes
Degree of protection (IP)	IP20

Dimension drawing

R40,R63

Limits 190,120

