




F&F Filipowski sp.k., ul. Konstantynowska 79/81, 95-200 Pabianice, tel.: +48 (42) 214 90 37, e-mail: biuro@fif.com.pl, www.fif.com.pl



ST63-40

Contactor 63A 230V 4NO contacts

Index: ST63-40

Modular contactor

Rated current: 63 A

Voltage: 230 V AC

AC1 switching power: 24 kW

AC3 switching power: 8.5 kW

Electromagnetic contactor in a **modular housing** for direct mounting on a 35 mm DIN rail.



5 908312 594222 >

FUNCTIONING

DESCRIPTION

Functioning

Connect the voltage on the contactor's coil will switch the contact. Contactor's status is indicated by blinking red marker in the box. After a loss of power the contacts return to their original position.

TECHNICAL DATA

Rated operating voltage	185-265 V
Rated operation current	63 A
Rated excitation voltage	185-265 V
Number of contacts as normally open contact	4
Number of contacts as normally closed contact	0

Slider for hand switch	No
Width in number of modular spacings	3
Built-in depth	65 mm
Additional equipment possible	Yes
With day/night function	No
Voltage type (operating voltage)	AC
Voltage type (excitation voltage)	AC
Degree of protection (IP)	IP20
Utilization category according to EN IEC 60947-4-1	AC-7a/AC-7b
Max. incandescent lamp load	0 W
Max. load fluorescent lamp	0 VA
Max. load fluorescent lamp (Duo circuit)	0 VA
Max. load fluorescent lamp (parallel compensated)	0 VA

Manual

CE Declaration