



F&F Filipowski sp.k., ul. Konstantynowska 79/81, 95-200 Pabianice, tel.: +48 (42) 214 90 37, e-mail: biuro@fif.com.pl, www.fif.com.pl



ST40-40

Contactor 40A 230V contacts 4NO

Index: ST40-40

Current 40 A. Voltage 230 V AC. Power AC1 16 kW. Power AC3 5.5 kW.

Electromagnetic contactors in modular case for direct mounting on rail 35mm.



5 908312 594192 >

FUNCTIONING

DESCRIPTION

Functioning

Connect the voltage on the contactor's coil will switch the contact. Contactor's status is indicated by blinking red marker in the box. After a loss of power the contacts return to their original position.

TECHNICAL DATA

Rated operating voltage	185-265 V
Rated operation current	40 A
Rated excitation voltage	185-265 V
Number of contacts as normally open contact	4
Number of contacts as normally closed contact	0
Slider for hand switch	No
Width in number of modular spacings	3
Built-in depth	65 mm
Additional equipment possible	Yes
With day/night function	No

Voltage type (operating voltage)	AC
Voltage type (excitation voltage)	AC
Degree of protection (IP)	IP20
Utilization category according to EN IEC 60947-4-1	AC-7a/AC-7b

Manual

CE Declaration