




F&F Filipowski sp.k., ul. Konstantynowska 79/81, 95-200 Pabianice, tel.: +48 (42) 214 90 37, e-mail: biuro@fif.com.pl, www.fif.com.pl



ST25-20

Contactor 25A 230V 2NO contacts

Index: ST25-20

Current 25 A. Voltage 230 V AC. Power AC1 4 kW. Power AC3 1.3 kW.

Electromagnetic contactors in modular case for direct mounting on rail 35mm.



FUNCTIONING

DESCRIPTION

Functioning

Connect the voltage on the contactor's coil will switch the contact. Contactor's status is indicated by blinking red marker in the box. After a loss of power the contacts return to their original position.

TECHNICAL DATA

Rated operating voltage	185-265 V
Rated operation current	25 A
Rated excitation voltage	185-265 V
Number of contacts as normally open contact	2
Number of contacts as normally closed contact	0
Slider for hand switch	No
Width in number of modular spacings	2
Built-in depth	65 mm
Additional equipment possible	Yes
With day/night function	No

Voltage type (operating voltage)	AC
Voltage type (excitation voltage)	AC
Degree of protection (IP)	IP20
Utilization category according to EN IEC 60947-4-1	AC-7a/AC-7b

Manual

CE Declaration