



F&F Filipowski sp.k., ul. Konstantynowska 79/81, 95-200 Pabianice, tel.: +48 (42) 214 90 37, e-mail: biuro@fif.com.pl, www.fif.com.pl



ST40-22

Contactor 40A, 230V, contacts 2NO + 2NC

Index: ST40-22

Stycznik modułowy.
Prąd 40 A.
Napięcie 230 V AC
Moc łączeniowa AC1 16 kW
Moc łączeniowa AC3 5,5 kW

Stycznik elektromagnetyczny w obudowie modułowej do bezpośredniego montażu na szynie 35 mm.



5 908312 599470 >

FUNCTIONING

DESCRIPTION

Działanie

Podanie napięcia zasilania **na cewkę stycznika** spowoduje **przełączenie styku**. Stan załączenia stycznika jest sygnalizowany czarnym znacznikiem w okienku. **Po zaniku napięcia** zasilania styki powracają do pierwotnej pozycji.

TECHNICAL DATA

Rated operating voltage	185-265 V
Rated operation current	40 A
Rated excitation voltage	185-265 V
Number of contacts as normally open contact	2
Number of contacts as normally closed contact	2
Slider for hand switch	No

Width in number of modular spacings	3
Built-in depth	65 mm
Additional equipment possible	Yes
With day/night function	No
Voltage type (operating voltage)	AC
Voltage type (excitation voltage)	AC
Degree of protection (IP)	IP20
Utilization category according to EN IEC 60947-4-1	AC-7a/AC-7b

Manual

REACH Declaration

RoHS Declaration