

Specifications



Eaton 277376

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, DILM7-10 - DILM38-10

General specifications

PRODUCT NAME	Eaton Moeller® series DILM auxiliary contact module
CATALOG NUMBER	277376
MODEL CODE	DILM32-XHI11
EAN	4015082773762
PRODUCT LENGTH/DEPTH	45 mm
PRODUCT HEIGHT	38 mm
PRODUCT WIDTH	36 mm
PRODUCT WEIGHT	0.038 kg
CERTIFICATIONS	UL 508 VDE 0660 CE CSA UL IEC/EN 60947-4-1 CSA-C22.2 No. 14-05 IEC/EN 60947 CSA Class No.: 3211-03 CSA File No.: 012528 UL Category Control No.: NKCRC UL File No.: E29184
PRODUCT TYPE	Accessory



Powering Business Worldwide

Features Functions

FEATURES	Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L)
FUNCTIONS	For standard applications
FITTED WITH:	Interlocked opposing contacts
NUMBER OF POLES	Two-pole
ELECTRIC CONNECTION TYPE	Screw connection

Ambient conditions, mechanical

SHOCK RESISTANCE	5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
-------------------------	--

General

DEGREE OF PROTECTION	IP20
LIFESPAN, ELECTRICAL	1,300,000 Operations (at 230 V, AC-15, 3 A)
MODEL	Top mounting
MOUNTING METHOD	Front fastening
CONNECTION	Screw terminals
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
TYPE	Front mounting auxiliary contact

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Terminal capacities

**TERMINAL CAPACITY
(FLEXIBLE WITH
FERRULE)** 1 x (0.75 - 2.5) mm²
2 x (0.75 - 2.5) mm²

**TERMINAL CAPACITY
(SOLID)** 1 x (0.75 - 2.5) mm²
2 x (0.75 - 2.5) mm²

**TERMINAL CAPACITY
(SOLID/STRANDED AWG)** 18 - 14

SCREWDRIVER SIZE 0.8 x 5.5/1 x 6 mm,
Terminal screw, Standard
screwdriver
2, Terminal screw, Pozidriv
screwdriver

TIGHTENING TORQUE 1.2 Nm, Screw terminals

Electrical rating

**RATED OPERATIONAL
CURRENT (IE)** 3 A at 110 V, DC L/R ≤ 15
ms (with 1 contact in
series)
10 A at 24 V, DC L/R ≤ 15
ms (with 1 contact in
series)
6 A at 60 V, DC L/R ≤ 15 ms
(with 1 contact in series)
1 A at 220 V, DC L/R ≤ 15
ms (with 1 contact in
series)

**RATED OPERATIONAL
CURRENT (IE) AT AC-15,
220 V, 230 V, 240 V**

6 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-15,
380 V, 400 V, 415 V**

4 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-15,
500 V**

1.5 A

**RATED OPERATIONAL
CURRENT (IE) AT DC-13,
24 V**

2.5 A

**RATED OPERATIONAL
CURRENT (IE) AT DC-13,
60 V**

1 A

**RATED OPERATIONAL
CURRENT (IE) AT DC-13,
110 V**

0.5 A

**RATED OPERATIONAL
CURRENT (IE) AT DC-13,
220 V, 230 V**

0.25 A

**RATED INSULATION
VOLTAGE (UI)**

690 V

**RATED OPERATIONAL
VOLTAGE (UE) AT AC -
MAX**

500 V

Short-circuit rating

**SHORT-CIRCUIT
PROTECTION RATING** Max. 10 A gG/gL, Fuse,
Without welding, Auxiliary
contacts

**SHORT-CIRCUIT
PROTECTION RATING
WITHOUT WELDING** 10 A gG/gL, 500 V, Max.
Fuse, Contacts

Conventional thermal current I_{th}

**CONVENTIONAL
THERMAL CURRENT I_{TH}
AT 60°C (3-POLE, OPEN)** 16 A

Switching capacity

SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)	1 A, 250 V DC, (UL/CSA) 10 A, 600 V AC, (UL/CSA)
---	---

SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	P300, DC operated (UL/CSA) A600, AC operated (UL/CSA)
--	--

Safety

SAFE ISOLATION	400 V AC, Between coil and auxiliary contacts, According to EN 61140 400 V AC, Between auxiliary contacts, According to EN 61140
-----------------------	---

Contacts

CONTROL CIRCUIT RELIABILITY	$\lambda < 5 \times 1/10^7$ (1 failure at 2,000,000 operations for $U_e = 24$ V DC, $U_{min} = 17$ V, $I_{min} = 5.4$ mA)
--	--

NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
--	---

NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
--	---

NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1
--	---

Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID	0 W
--	-----

HEAT DISSIPATION CAPACITY PDISS	0 W
--	-----

HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT PVID	0.16 W
---	--------

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	4 A
--	-----

STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS	0 W
--	-----

10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
--	---

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
---	---

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
---	---

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
---	---

10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
---	---

10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
-----------------------	--

10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

CATALOGS

[SmartWire-DT Catalog](#)

[Product Range Catalog](#)
[Switching and protecting motors](#)

DECLARATIONS OF CONFORMITY

[eaton-accessory-declaration-of-conformity-uk251276en.pdf](#)

[eaton-accessory-declaration-of-conformity-eu250793en.pdf](#)

DRAWINGS

[eaton-contactors-frame-dilm-dimensions.eps](#)

[eaton-contactors-module-dilm-dimensions.eps](#)

[eaton-contactors-contact-dilm-accessory-3d-drawing.eps](#)

ECAD MODEL

[ETN.277376.edz](#)

INSTALLATION INSTRUCTIONS

[eaton-contactors-dila-dilm7-15-dilmp20-il03407013z.pdf](#)

INSTALLATION VIDEOS

[WIN-WIN with push-in technology](#)

MCAD MODEL

[eaton-contact-blocks-mcad-drawings-dil-m32-xhi-2.dwg](#)

[dil_m32_xhi_2.stp](#)

WIRING DIAGRAMS

[2100SWI-119](#)

[eaton-contactors-contact-sdainl-combination-wiring-diagram.eps](#)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

