

LUNARIX 2

SLIP007018

LED luminaire LUNARIX 2 with the possibility of changing the light color (CCT), with a power of 4 W, high light efficacy 100 lm/W. Thanks to the ability to change the color temperature (CCT) in the range 2700/4000/6500K, we can adjust the light color depending on our needs and preferences. The luminaire has lenses on both sides, so it shines up and down. It has a high IP54 rating, making it ideal for use in rooms with high humidity. It also stands out for its very high colour rendering index RA>90. Narrow beam angle 45° gives directional light so that selected objects or surfaces can be better exposed. Designed for surface mounting.

CCT

CRI
>90

IP54



Power **4 W**
Luminous flux* **400 lm (360°)**
Colour of light **CCT**
Degree of protection (IP) **IP54**

Voltage **230 V**
Colour temperature **2700/4000/6500 K**
Beam angle **45 °**

Technical data

Code	SLIP007018
Power	4 W
Nominal current	32 mA
Voltage	230 V
Energy consumption	4 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Useful luminous flux*	400 lm (360°)
Luminous flux**	300 lm (360°)
Lamp efficacy	100 lm/W
Luminous intensity	220 cd
Colour temperature	2700/4000/6500 K
Colour of light	CCT
Beam angle	45 °
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	POLIWĘGLAN
Degree of protection (IP)	IP54
Colour	Black
Dimension (AxBxC)	110x100x40 mm
For use	Outside/Inside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC

Related documents



 User manual



 Declaration of Conformity

