

SINCE 1978



LEADING LIGHT

# Product Datasheet

vkleadinglight.gr

Smol

VK/04436/B/W


Recessed ceiling light led, 1W, 3000K, 65lm, 24°, CRI>90, IP20, ø2.3cm, black



IP20



## Dimensions



## Gallery



Recessed Ceiling Light Led

Smol

| Model        | Power (W) | Beam Angle (°) | Color Temperature (K) | Light Output (lm) | Dimensions (mm) |
|--------------|-----------|----------------|-----------------------|-------------------|-----------------|
| VK/04436/B/W | 1         | 24             | 3000                  | 65                | 23x35           |
| VK/04436/B/W | 1         | 24             | 4000                  | 65                | 23x35           |
| VK/04436/B/W | 1         | 24             | 5000                  | 65                | 23x35           |
| VK/04436/B/W | 1         | 24             | 6000                  | 65                | 23x35           |

## Downloads



| Technical Specifications |                                                                                   |
|--------------------------|-----------------------------------------------------------------------------------|
| Kelvin                   | 3000K                                                                             |
| Power                    | 1W                                                                                |
| Voltage                  | 100-260V                                                                          |
| Fitting                  | Recessed dark ceiling                                                             |
| Type                     | Downlight LED                                                                     |
| Safety class             |  |
| Light source             | OSRAM SMD                                                                         |
| IP Rating                | <b>IP20</b>                                                                       |
| CRI                      | CRI>90                                                                            |
| Dimmable                 |  |
| Lifetime                 | 20.000hrs                                                                         |
| Driver                   | Built-in DC 2-4V 300mA                                                            |
| Working temperature      | < 45°C                                                                            |
| PAGE                     | 212 Technical 2024                                                                |
| NICKNAME                 | Smol                                                                              |

| Physical Specifications           |                                                       |
|-----------------------------------|-------------------------------------------------------|
| Recessed ceiling                  | Yes                                                   |
| Color                             | Black matt                                            |
| Material                          | Aluminium                                             |
| Width                             | ø2.3cm                                                |
| Length                            | ø2.3cm                                                |
| Height                            | 3.5cm                                                 |
| Net weight of product (kg)        | 0.03                                                  |
| Gross weight with inner box (kg)  | 0.05                                                  |
| Gross weight with master box (kg) | 2.80                                                  |
| Cut out                           | ø2cm H3.5cm (the cut hole also fits the light driver) |

| Illumination Data  |                                                                                   |
|--------------------|-----------------------------------------------------------------------------------|
| Lumen              | 65lm                                                                              |
| Beam angle         | 24°                                                                               |
| Lighting direction |  |
| Dark light         | Yes                                                                               |

| Packing Info |       |
|--------------|-------|
| Pcs/carton   | 50pcs |

| Certification & Warranty |         |
|--------------------------|---------|
| Guarantee                | 3 years |

Energy Label



VK LEADING LIGHT  
VK/04436/B/W

A

B

C

D

E

F

G

1

kWh/1000h



2019/2015

F