



Compact. Light and well-balanced. Now with super driving power for maximum sanding performance!



### Block Belt Sander BBS/S

The sanding belt is located flush on the left side to allow surfaces to be sanded "right down to the corner". A fine adjustment for the rollers prevents running off on the side. Spring clamping system for easy replacement of belts without tool: Packed in a sturdy plastic carrying case together with five each 120 grit and 240 grit sanding belts.

#### Technical data:

220 - 240 V, 150 W. 50 - 60 Hz. Sanding belt 40 x 265 mm. Sanding surface 60 x 40 mm. Belt speed 160 m/min. Weight 700 g. Housing of fibreglass reinforced POLYAMIDE. Insulated to class 2.

#### NO 28 526

Five each 120 grit and 240 grit sanding belts are included.



#### Standard corundum sanding belts for BBS/S block belt sander

Various grits of high density, on a powerful backing, cover a wide range of applications. Used on sand metals, non-ferrous metals, wood and plastic. Size 40 x 265 mm.

|           |      |     |        |
|-----------|------|-----|--------|
| NO 28 922 | grit | 80  | 5 each |
| NO 28 924 | grit | 120 | 5 each |
| NO 28 926 | grit | 180 | 5 each |
| NO 28 928 | grit | 240 | 5 each |



The BBS/S block belt sander is supplied in a new, high-quality PP storage case. It has a strong frame, is extremely stable and large enough to repack in the case without "fiddling around". With lateral sticker for identification of the content.



Also for stationary use. Screw clamp included.