Long neck Angle Grinder LWS

220-240 VOLT

A carborundum grinding disc of grit 60, a fan sander of grit 100 and a reinforced cutting disc are included.

Features include a special, balanced motor. Used on steel, non-ferrous metals, glass, ceramics and wood too.

Technical data:
Disc diameter 50mm Ø. Mains voltage 220 – 240V, 50/60Hz, 100W max power consumption. 13,000rpm. Stable head of die-cast alu and POLYAMIDE main housing. Length 280mm, and weight approx 550g. Run down time less than 1 second. Insulated to class 2.
No 28 547

Corundum grinding disc, 50mm diameter, for LWS
Used for de-burring, grinding, sharpening and de-rusting steel and non-ferrous metals.
No 28 585 (60 grit)
No 28 586 (36 grit)



Silicon Carbide grinding disc, 50mm diameter, for LWS
Used on glass, stone, ceramics and very hard materials.
No 28 587 (60 grit)

Fan sander, 50mm diameter, for LWS
Standard corundum for superior stock removal on tempered cast iron, cast iron, stainless steel, non-ferrous metals, wood and plastic.
No 28 590 (100 grit)
No 28 591 (150 grit)

Corundum bound cutting disc for LWS
With woven reinforcing, ideal for cutting steel, non-ferrous metals, plastic and wood. 50mm diameter, 10mm bore and 1mm thick.
No 28 154

Backing disc for LWS
Self-adhesive type, for use with sanding discs and sanding fleece.

No 28 548		1 off

Corundum sanding discs
Self-adhesive type, used on flat and convex surfaces.

No 28 549	80 grit	5 off
No 28 550	120 grit	5 off
No 28 551	180 grit	5 off
No 28 552	240 grit	5 off

Sanding fleece for LWS
Self-adhesive type, used for cleaning, matting and sanding of steel, stainless, steel, non-ferrous metals. Also used for paint removal.

No 28 554	medium	5 off
No 28 555	fine	5 off