



With electronic speed control from 250 to 750 rpm.  
Also for wet sanding.

## Disc Sander TG 250/E

Sands long edges, end sections, radii, mitres and by turning work piece over - accurate flat surfaces at right angles. Used on soft and hard woods, non-ferrous metals, steel, plastics (Plexiglass and fibreglass), cork and rubber. A simple chart indicates the recommended speeds on different materials.

### Sturdy construction:

Main body of ribbed die-cast aluminium (not a steel tube or sheet metal construction). Table of die-cast aluminium with machined surface. Tilts 15° inwards and 45° outwards (a scale facilitates accurate adjustment). Table mitre gauge supplied as standard. Machined backing disc - driven by a twin ball bearing spindle. Standard, commercially available sanding discs fix firmly and can be replaced quickly. A dust collection adapter for attaching a vacuum cleaner/dust extractor is included.

### Technical Data:

220 - 240 Volt with drive via toothed belt (reduction ratio 7.3:1). Electronic speed control approx. 250 - 750 rpm, disc diameter 250 mm. Max. sanding height 135 mm, table 275 x 105 mm (tilts 15° in, 45° out). Overall size without table 330 x 280 x 230 mm. Complete with mitre gauge and 2 each sanding discs of 100 grit and 240 grit.

NO 28 060



- ❶ Optional with coolant system for wet sanding of glass, stone, tiles and steel.
- ❷ Table size: 275 x 105 mm with slot for mitre gauge and tilts up to 45°.
- ❸ 250 mm disc, surface machined and with double ball bearing spindle.



Equipped with vacuum cleaner adapter for working in a clean, dust-free environment.

**Self-adhesive Sanding Discs (diameter 250 mm)**

Industrial quality: Carborundum with artificial bonding agent. For sanding soft and hard woods, chip board, fiber plates, non-ferrous metals, steel, plastics, cork, rubber and minerals.

|                  |          |        |
|------------------|----------|--------|
| <b>NO 28 970</b> | Grit 80  | 5 pcs. |
| <b>NO 28 972</b> | Grit 150 | 5 pcs. |
| <b>NO 28 974</b> | Grit 240 | 5 pcs. |

**Self-adhesive Waterproof Sanding Discs (diameter 250 mm)**

Aluminium oxide with artificial bonding agent. For sanding non-ferrous metals, steel, glass, PC cards, plastics and ceramics. May be used with the coolant system.

|                  |          |        |
|------------------|----------|--------|
| <b>NO 28 976</b> | Grit 320 | 5 pcs. |
|------------------|----------|--------|

**Wet sanding and cutting of glass, stones and tiles.**  
**With MBS 240/E and TG 250/E.**

**Coolant Container**

Plastic container with stop cock, 100 cm tubing and mounting bracket/screws. Holds 1 litre.

**NO 28 188**

**Coolant Collection Tray**

Size 420 x 310 x 15 mm. Includes gasket for sealing the fixing holes of the machine. With 50 cm discharge tube. The tray is undrilled and may be used on other machines too.

**NO 28 189**