



AGM JUMP STARTER

SOSBOOST ⚡ 12/24 V 🔌 3200/1600 CA



+++

Our AGM batteries, with pure lead are extremely efficient thanks to their ability to deliver energy at high amperage almost instantaneously (cranking amps is what is required to make the vehicle start).

The internal fuse protects the batteries against shortcircuits.

Starting cables (double insulation) with an optimal length and extremely flexible benefit from a high conductivity as well as a perfect shape resistant to frequent handling.

The single-piece moulded case in polyethylene of 5 mm, unbreakable (life time warranty), assures excellent resistance to shocks and everyday uses.



300A



TECHNICAL INFORMATION

MODEL	12/24 V 1600/800 CA	12/24 V 2400/1200 CA	M 12/24 V 3200/1600 CA
PART NUMBER	761006	760008	960000
VOLTAGE (DC)	12/24 V	12/24 V	12/24 V
CRANKING AMPS (CA)	1600/800	2400/1200	3200/1200
CABLE LENGTH	1,35 m	1,35 m	1,95 m
CABLE CROSS SECTION	35 mm ²	50 mm ²	70 mm ²
AUTOMATIC CHARGER	4 A	4 A	7 A



PACKAGING INFORMATION

MODEL	12/24 V 1600/800 CA	12/24 V 2400/1200 CA	M 12/24 V 3200/1600 CA
NET WEIGHT	20,5 kg	24,8 kg	55 kg
DIMENSIONS (L x W x h) mm	530 x 160 x 480	530 x 160 x 480	470 x 340 x 970

HOW TO CHOOSE

HOW TO CHOOSE			12 V								24V					
PART NUMBER	MODEL	VOLTAGE	<125	150	175	250	300	350	500	100	250	500	1000	1500	2000	
			HP* = CHECK YOUR ENGINE HP - LEGEND: ■ NORMAL ■■ INTENSIVE													
761006	12/24 V 1600/800 CA	12/24 V	■■	■■	■■	■■	■■	■		■■	■■	■				
760008	12/24 V-2400/1200 CA	12/24 V	■■	■■	■■	■■	■■	■■	■■	■■	■■	■■	■	■		
960000	12/24 V-3200/1600 CA	12/24 V	■■	■■	■■	■■	■■	■■	■■	■■	■■	■■	■■	■		

AUXILIARY CONNECTOR BUILT ON THE BOOSTER	
 Portable 860014	 Mobile 860022

OPTIONAL AUXILIARY CABLES		
PLUG	PN FOR PORATBLE	PN FOR MOBILE
	860037	860035
	860016	860034
	860015	860024
	860032	860033