

THINNER 20

Thinner for CONIPUR Line Paintings

Product description

THINNER 20 is a mixture of different solvents.

Fields of application

THINNER 20 can be used to dilute the line paintings CONIPUR 3100 and CONIPUR 8150

Properties

THINNER 20 can be mixed with CONIPUR 3100 and CONIPUR 55 (N) and reduces their viscosity. This may be necessary in case of [low temperatures](#).

Technical Data

Density	DIN 51757, at 23 °C	g/cm ³	0.88
Viscosity	DIN 51562, at 23 °C	mPas	1
Flash point	DIN 51755	°C	> 24
Boiling range	DIN 53171	°C	> 135
Solubility	in most organic solvents	g/l	∞

Above figures are guide values and should not be used as a base for specifications!

Application method

The [A](#) and [B](#) component of the [line painting](#) are [mixed](#) in the correct proportions as mentioned in the Technical Data Sheet and regulated to the adequate viscosity by [adding](#) THINNER 20.

Please note the [maximum](#) quantity of solvent as mentioned in the Technical Data Sheet.

Pack size

THINNER 20 is supplied in 16.5 kg cans.

Storage

Store in unopened cans under dry conditions at a temperature range of 5 - 25 °C.

Do not expose to direct sunlight.

Before use, please see "best before" date on the pail / drum.

Safety precautions

For protective measures, transport regulations and waste management please refer to the Material Safety Data Sheet of the product.