

# THINNER 32

## Solvent for CONIPUR Sealing Lacquers

### Product description

THINNER 32 is a solvent for the dilution of sealing lacquers.

### Fields of application

THINNER 32 can be used for the dilution of the sealing lacquers CONIPUR 2200, CONIPUR 2210 and

CONIPUR 67 as well as the line painting CONIPUR 8150.

### Properties

THINNER 32 can be mixed with above mentioned products and reduces their viscosity. This can be necessary in case of low temperatures.

## Technical Data

<b>Density</b>	DIN 51757, at 23 °C	g/cm <sup>3</sup>	approx. 0.97
<b>Viscosity</b>	DIN 51562, at 23 °C	mPas	approx. 1
<b>Flash point</b>	DIN 51755	°C	approx. 42
<b>Boiling range</b>	DIN 53171	°C	140-150
<b>Solubility</b>	in water in most organic solvents	g/l g/l	190 ∞

***Above figures are guide values and must not be used as a base for specifications!***

### Application method

The **A** and **B** component of the sealing lacquer or line-painting are **mixed** in the correct proportions as mentioned in the Technical Data Sheet and regulated to the adequate viscosity by **adding** THINNER 32.

Please note the **maximum** quantity of solvent as mentioned in the Technical Data Sheet.

### Pack size

THINNER 32 is supplied in 5 kg cans.

### Storage

Store in unopened cans under dry conditions at a temperature range of 15 - 25 °C.

Do not expose to direct sunlight.

Before use, please see "best before" date on the pail / drum.

### Safety precautions

For protective measures, transport regulations and waste management please refer to the Material Safety Data Sheet of the product.