



Cosmos Lac AE

1 Pindou str.
17672 Kallithea, Athens, Greece.
Tel.: +30 2109570222 -
Fax: +30 2109566671
factory@cosmoslac.com
www.cosmoslac.com

Technical Data Sheet

PRODUCT	COSMOS LAC Wheel Rim 326/327/328
DESCRIPTION/ USES	High gloss metallic paint with anticorrosive and scratch resistance. It is a quick dry special paint, for enhanced durability under the wear and tear inflicted on a car wheel.
Viscosity	18-25 sec (Flow Cup DIN4, 20°C)
Density	0.6-0.8 g/L (Density Cup 100cm ³ /20°C, ASTM D – 1475)
Solids w/w	15-20%
VOC content	610 g/L
Flash Point	-104 °C (based on propellant)
Drying time	Touch (20°C, Humidity<65%): 5-10min Through dry (20°C, Humidity <65%) : 1h Maximum hardness: 24 hours
Coverage	5m ² /L
Can Pressure	4bar (20 °C) , 8 bar (50 °C)
Contents	400ml
Application	Remove all dust, rust and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 30cm from the surface. Try the spray on testing surface. For better results apply 2-3 thin coats, 3-5 min apart. Best application temperature : 20 °C - 25 °C
After use	Spray holding the can inverted for 3''. Clean the caps with solvent.
Storage	5-35°C. Do not put in vehicles.

ISSUED 27 November 2017, factory@cosmoslac.com