

ENDURANCE HD

Commercial vehicles batteries



SHD technology



Resistance to extreme vibration



Resistance to extreme temperatures



Maintenance free



Leakage free



Bus



Loader



Semi-Trailer



Heavyweight with tail lift

- Double lid with labyrinth system and flame arrestor – Sealed maintenance-free batteries
- Punched positive and ConCast (Continuous Casting) technology negative grids
- Longer lifespan and high resistance to cycling

- Polyethylene separators with high mechanical resistance
- Very good vibration resistance due to the very tight group fixation in to the cell
- Calcium-Calcium technology with very low water consumption

Applications: commercial vehicles, agricultural and construction equipment with intensive use
(e.g., vibrations, deep discharge, additional electrical consumers, etc.)

Code	Case size	Capacity	Cold Cranking Ampere (A)-18°C EN U _{10s} ≥7,5V	Base holddown	No. of rows Pieces on pallet	Dimensions (mm)	Layout
EHD120	C13	12V 120Ah	900	B01	3/36	L : 345 W : 175 H : 238	
EHD130	MB14	12V 130Ah	850	B03	3/24	L : 513 W : 190 H : 217	
EHD150	MB14	12V 150Ah	900	B03	3/24	L : 513 W : 190 H : 217	
EHD180	M15	12V 180Ah	1100	B00	3/18	L : 513 W : 223 H : 217	
EHD200	M15	12V 200Ah	1150	B00	3/18	L : 513 W : 223 H : 217	
EHD220	M16	12V 220Ah	1100	B00	3/18	L : 518 W : 273 H : 236	
EHD235	M16	12V 235Ah	1200	B00	3/18	L : 518 W : 273 H : 236	